



---

# MUNICIPAL DEVELOPMENT STANDARDS

STANDARD DRAWINGS

October 2020

Planning & Engineering

---

## Roadways

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
1-100	Urban Residential Local Roadways	5	2020-06-22
1-101	Urban Residential Collector Roadways	6	2020-06-22
1-102	Urban Industrial / Commercial Roadways	6	2020-06-22
1-103	Urban Arterial Roadways	6	2020-06-22
1-104	Typical Lane Cross Section	4	2020-06-22
1-106	Typical Residential Cul-de-sac	5	2020-06-22
1-107	Typical Industrial/Commercial Cul-de-sac	4	2020-06-22
1-200	Typical Cross Section Rural Roads	4	2020-06-22
1-201	Industrial / Commercial Approaches (Rural)	2	2018-11-19
1-202	Typical Rural Utility Layout	5	2020-05-04
1-203	Typical Rural Hydrant Shoulder Widening Layout	4	2020-05-04
1-204	150mm Steel Roadway Bollard	2	2020-02-27
1-300	Pavement Markings	2	2020-05-04
1-301	Traffic Signage	5	2020-06-29
1-302	Traffic Signage	2	2020-02-27
1-303	Hand Applied Markings	2	2020-05-04
1-400	Gutter and Butt Joint Milling	3	2020-05-04
1-500	Roundabout Cross-Section	1	2020-03-03
1-501	Roundabout Plan View and Landscaping Zones	2	2020-06-23

## Concrete Work

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
2-100	Standard 150 mm Curb with 250 mm Gutter	6	2020-05-04
2-101	Standard 200 mm Curb with 250 mm Gutter	6	2020-05-04
2-102	Rolled Face Curb and Gutter	6	2020-05-04
2-103	Standard Barrier Curb	5	2020-05-04
2-104	Pinned Curb Median Detail	5	2020-06-22
2-105	Rolled Face Curb, Gutter, and Monolithic Sidewalk	6	2020-06-22
2-106	Straight Face Curb, Gutter and Monolithic Sidewalk	5	2020-06-22
2-107	1.5m Separate Sidewalk	6	2020-05-04
2-108	Mono Service Strip and Concrete Edger	5	2020-05-04
2-109	Commercial / Lane Crossing – Monolithic Sidewalk	9	2020-09-29
2-110	Commercial / Lane Crossing – Separate Sidewalk	9	2020-09-21
2-111	Residential Apron Crossing Mono Sidewalk	0	2020-09-21
2-112	Residential Apron Crossing Separate Sidewalk	0	2020-09-21
2-113	Trench Drain	4	2020-09-21
2-200	Curb Ramp	6	2020-09-30
2-201	Typical Dropped Gutter Lip for Two Stage Paving	4	2020-03-05
2-202	Type F-51 Catch Basin Curb Finishing Detail	3	2020-03-05
2-203	Typical Median	4	2020-05-04
2-204	“CC” Stamp	2	2020-03-05
2-205	Concrete Drainage Swale (Roadway)	4	2020-05-04

## Manhole Details

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
3-100	Precast Manhole for Pipes up to 525 mm Diameter	7	2020-03-06
3-101	Precast Manhole for Pipes 600 mm to 900 mm Diameter	8	2020-03-06
3-102	Typical T-Riser Manhole for Pipes 1050 mm Diameter and Larger	9	2020-05-04
3-103	Internal Drop Manhole	7	2020-03-06
3-104	Perched Manhole	0	2019-07-02
3-105	Manhole Penetrations and Design	2	2020-03-06

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
3-200	Non-Floating Manhole Frame Adjustment Detail	4	2020-05-04
3-201	Safety Platform	4	2020-05-04
3-202	F-80 Manhole Frame	1	2016-04-14
3-203	F-80 Manhole Adjustment Detail	2	2020-03-06
3-204	TF-80LSAN Sanitary Sewer Cover (City Logo)	6	2020-03-06
3-205	TF-80LSTM Storm Sewer Cover (City Logo)	4	2020-03-06
3-206	Watertight Manhole Cover	3	2020-03-06
3-208	F-39 Frame and Locking Cover	1	2018-08-20
3-300	Typical Pipe Section Exfiltration Test	1	2020-03-06

## Trenching and Backfill

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
4-100	Trench Backfill	4	2020-03-06
4-101	Insulation Requirements	1	2020-03-06
4-102	Insulation Requirements Crossing Pipe Open to Atmosphere	0	2020-03-09
4-200	Pipe Zone Bedding Detail (Class A, B)	6	2020-05-04
4-300	Pipe Support	1	2018-03-23

## Storm Drainage

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
5-100	900 mm Dia. Catch Basin c/w Frame and Cover	7	2018-03-23
5-101	1200 mm Dia. Catch Basin c/w F-51 Frame and Cover with Two Piece Side Inlet	4	2018-11-23
5-200	Wick Drain Connection to Catch Basin	4	2020-05-04
5-300	Poured Concrete Outfall Structure	5	2020-03-09
5-301	Metal Culvert	1	2018-11-23
5-302	Bar Screen for Outlet Structure Detail	1	2018-11-26
5-303	Bar Screen for Inlet Structure Detail	1	2018-11-26
5-304	Rock Rip-Rap Detail for Metal Culverts or Open Channels	1	2018-11-26
5-400	Inlet/Outlet Indicator Post Detail	5	2020-05-04
5-401	Stormwater Storage Wetland Sign	4	2020-03-10
5-402	Stormwater Storage Pond Sign	4	2020-03-10
5-403	Stormwater Storage Site Sign	4	2020-03-10
5-404	Stormwater Storage Channel Sign	4	2020-03-10
5-405	Stormwater Storage Site Sign Details	5	2020-05-04
5-406	Typical Notice Sign	3	2020-05-04
5-500	Typical Stormwater Storage Pond	0	2019-01-10
5-501	Typical Stormwater Storage Pond Forebay	0	2019-01-09

## Water Distribution

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
6-100	Water Valve Installation	5	2020-03-10
6-101	Hot Tapping Connection	6	2020-06-22
6-102	Hydrant Installation	7	2020-05-05
6-200	Permanent Blow Off Valve Detail	7	2020-05-05
6-201	Valve Adjustment Detail	3	2020-03-10
6-300	Poured Concrete Thrust Blocks for Horizontal Tees and Bends	4	2020-03-10
6-301	Poured Concrete Thrust Blocks for Vertical Bends (Downward Thrust)	4	2020-03-10
6-302	Poured Concrete Thrust Blocks for Vertical Bends (Upward Thrust)	4	2020-03-10
6-303	Poured Concrete Thrust Blocks for Dead-ends	4	2020-03-10
6-304	Poured Concrete Thrust Blocks for Dead-ends in Disturbed Soil	1	2020-03-10

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
6-400	Anode Installation at Hydrant	3	2018-03-22
6-401	Typical Anode Installation for Metallic Fittings used with PVC Water Mains	3	2018-03-22

## Sanitary, Storm, and Water Service Connections

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
7-100	Typical Lateral Service Location Detail	8	2020-06-22
7-101	Residential Lateral Service Detail	7	2020-06-22
7-102	Multi-family Service Detail with Storm Service	5	2020-06-22
7-103	Multi-family Service Detail	5	2020-06-22
7-104	Commercial Service Detail with Storm Service	4	2020-06-22
7-105	Commercial Service Detail	4	2020-06-22
7-106	Service Connection Details for Sewer Manhole in Cul-de-Sac	2	2020-06-22
7-200	Residential Non-Riser Type Sanitary Service Connection	5	2020-06-22
7-201	Residential Riser Type Sanitary Service Connection	4	2020-06-22
7-202	Multi-family Sanitary Inspection Chamber	7	2020-06-22
7-203	Commercial / Industrial Sanitary Inspection Manhole	6	2020-06-22
7-204	Metal Driveway Box	2	2020-05-05
7-300	Residential Non-Riser Type Storm Service Connection	5	2020-06-22
7-301	Residential Riser Type Storm Service Connection	4	2020-06-22
7-302	Weeping Tile Discharge to Storm Service	4	2020-06-22
7-303	Granular Drainage Discharge to Storm Service	4	2020-06-22
7-304	Granular Drainage Overland Discharge If Storm Service Not Available	4	2020-05-05
7-305	Weeping Tile Overland Discharge If Storm Service Not Available	4	2020-05-05
7-400	Residential Water Service Connection	4	2020-03-11
7-401	Service Valve Rod for 20 mm, 25 mm, 38mm, 50 mm Curb Stops	0	2011-02-22
7-402	Service Box	5	2020-06-22

## Lot Grading


DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
8-100	Lot Grading Back to Front Drainage	6	2020-05-05
8-101	Lot Grading Split Drainage	6	2020-05-05
8-102	Shared Drainage Between Lots	3	2020-06-22
8-103	Concrete Between Driveways	3	2020-05-05
8-200	Concrete Drainage Swale (Landscaping)	6	2020-03-11

## Landscaping

DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
9-100	Standard Trail	4	2020-06-22
9-101	Root Barrier Section and Elevation	1	2020-03-11
9-102	Trail Seating Node	1	2020-03-17
9-103	Nature Trail	1	2020-03-17
9-104	Play Safe 18 mo to 5 yrs	2	2020-05-05
9-105	Play Safe Sign 5 Years to 12 Years	0	2020-03-15
9-200	Wooden Fence	3	2018-12-04
9-201	Chain-link Fence & Gate	5	2020-03-12
9-202	6" x 6" Wood Bollard	4	2020-03-12
9-203	150 mm Steel Landscaping Bollard	5	2020-05-05
9-204	Single Traffic Control Gate	4	2020-03-12
9-205	Paired Traffic Control Gates	2	2019-06-26
9-206	Steel Pipe Gate	2	2020-03-12




DRAWING NUMBER	DESCRIPTION	REVISION NUMBER	DATE
9-207	Chain Link Maintenance Gate	2	2020-03-12
9-208	Wooden Post and 3 Rail Fence	2	2020-03-12
9-209	Noise Attenuation Fence	4	2020-05-05
9-300	Tree Grate 1500 mm	1	2020-05-05
9-301	Typical Berm	5	2020-05-05
9-302	Wire Basket Tree Spade Planting Tree Staking & Mulching	1	2020-03-12
9-303	Typical Container Planting	1	2020-03-12
9-304	Typical Vault Planting	1	2020-03-12
9-305	Planting Bed Cross-Section	2	2020-05-05
9-400	Typical Park Bench	2	2018-12-04
9-401	Typical Picnic Table	4	2020-06-22
9-402	Garbage Receptacle	1	2017-03-02
9-403	Dog Waste Bag Dispenser	3	2020-03-12


This page intentionally left blank.



**NOTES:**




1. PAVEMENT STRUCTURES AS PER DESIGN STANDARDS SECTION 3.5.
2. MINIMUM CROSSFALL 2.5%, MAXIMUM CROSSFALL 4.0%.
3. CURB AND GUTTER TO BE ROLLED FACE WITH MONOLITHIC SIDEWALK. SEE DRAWING 1-205.

8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: N/A
5	22/06/20	Revised Notes		<b>URBAN RESIDENTIAL LOCAL ROADWAYS</b>		
4	27/02/20	Revised Notes				
3	21/03/18	Revised Notes				
2	22/11/16	Additional Notes				
1	12/04/16	Additional Notes & Dimensions				
NO.	DATE	REVISION	Scale: N.T.S.	<b>1-100</b>		Date: Feb. 22, 2011 Drawing #: 1-100




**NOTES:**

1. PAVEMENT STRUCTURES AS PER DESIGN STANDARDS SECTION 3.5.
2. MINIMUM CROSSFALL 2.5%, MAXIMUM CROSSFALL 4.0%
3. CURB AND GUTTER TO BE 150mm CURB WITH 250mm GUTTER. SEE DRAWING 1-100

8			<b>The City of Lloydminster</b>			
7						
6	22/06/20	Revised Notes		Checked by: 	Approved by: 	Drawn by: N/A
5	21/04/20	Added Dim. / Label				
4	27/02/20	Dimensions & Notes				
3	19/11/18	Changed Streetlight Position				
2	22/11/16	Additional Notes				
1	12/04/16	Changed Dimensions				
NO.	DATE	REVISION	Scale: N.T.S.	<b>URBAN RESIDENTIAL COLLECTOR ROADWAYS</b>		Date: Feb. 22, 2011
						Drawing #: 1-101





**NOTES:**

1. PAVEMENT STRUCTURES AS PER DESIGN STANDARDS SECTION 3.5.
2. MINIMUM CROSSFALL 2.5%, MAXIMUM CROSSFALL 4.0%.
3. COLLECTOR DETAILS TO BE REVIEWED AND APPROVED BY THE CITY.
4. CURB AND GUTTER TO BE 150mm CURB WITH 250mm GUTTER. SEE DRAWING 1-100.

8		
7		
6	22/06/20	Revised Note 2
5	21/04/20	Added Dim. / Label
4	27/02/20	Dimensions & Text
3	19/11/18	Changed Streetlight Position
2	22/11/16	Additional Notes
1	12/04/16	Revised Dimensions
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: N/A

**URBAN INDUSTRIAL / COMMERCIAL ROADWAYS**


Date: Feb. 22, 2011

Drawing #: 1-102

Scale: N.T.S.



**4 LANE URBAN DIVIDED ARTERIAL ROADWAY**



**4 LANE URBAN UNDIVIDED ARTERIAL ROADWAY**

**NOTES:**

1. PAVEMENT STRUCTURES AS PER DESIGN STANDARDS SECTION 3.5.
2. MINIMUM CROSSFALL 2.5%, MAXIMUM CROSSFALL 4.0%.
3. BERMS ARE REQUIRED ONLY WHERE ARTERIAL ROADWAY BACKS ON TO RESIDENTIAL LOTS. SEE DWG. 9-301 FOR BERM DETAILS.
4. CURB AND GUTTER TO BE 200mm CURB WITH 250mm GUTTER, SEE DWG. 2-101.

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: N/A


**URBAN ARTERIAL ROADWAYS**

Date: Feb. 22, 2011

Drawing #: 1-103




Scale: N.T.S.


8		
7		
6	22/06/20	Revised Drawing
5	27/02/20	Revised Drawing
4	02/07/19	Revised Drawing
3	11/19/18	Updated Notes & Resived Drawings
2	11/22/16	Additional Notes
1	18/04/16	Revised Dimensions
NO.	DATE	REVISION



**NOTES:**

1. PROVIDE FULL DEPTH ASPHALT PAVEMENT STRUCTURE TO ADJACENT HARD SURFACED PARKING AREAS.
2. PAVEMENT STRUCTURES AS PER DESIGN STANDARDS SECTION 3.5.
3. MINIMUM CROSSFALL 2.5%, MAXIMUM CROSSFALL 4.0%.
4. CENTRELINE CONCRETE SWALE TO BE CONSTRUCTED AS SHOWN IN DRAWING 2-205.

8				<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: N/A	
6				<b>TYPICAL LANE CROSS SECTION</b>			
5							
4	22/06/20	Revised Note 3					Date: Feb. 22, 2011
3	27/02/20	Revised Notes and Drawing					Drawing #: 1-104
2	11/19/18	Revised Notes and Drawing					
1	12/04/16	Revised Notes		Scale: N.T.S.			
NO.	DATE	REVISION					







OFFSET CUL-DE-SAC

STRAIGHT CUL-DE-SAC

**NOTES:**

1. THE MINIMUM SLOPE FROM THE CENTRE OF THE CUL-DE-SAC SHALL BE 1.0%.
2. THE MAXIMUM SLOPE FROM THE CENTRE OF THE CUL-DE-SAC SHALL BE 3.0%.
3. THE MINIMUM GUTTER GRADE SHALL BE 0.8%.

8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: N / A
5	22/06/20	Added "m" to dimensions		<b>TYPICAL RESIDENTIAL CUL-DE-SAC</b>	Date: Dec. 15, 2015 Drawing #: <b>1-106</b>	
4	04/05/20	Adjusted Font Size				
3	27/02/20	Changed Text & Dim.				
2	19/11/18	Additional Notes				
1	18/04/16	Changed dimensions				
NO.	DATE	REVISION	Scale: N.T.S.			







OFFSET CUL-DE-SAC

STRAIGHT CUL-DE-SAC

**NOTES:**

1. THE MINIMUM SLOPE FROM THE CENTRE OF THE CUL-DE-SAC SHALL BE 1.0%.
2. THE MAXIMUM SLOPE FROM THE CENTRE OF THE CUL-DE-SAC SHALL BE 3.0%.
3. THE MINIMUM GUTTER GRADE SHALL BE 0.8%.

8				<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>	
6				<b>TYPICAL INDUSTRIAL / COMMERCIAL CUL-DE-SAC</b>			
5							Date: <b>April 14, 2016</b>
4	22/06/20	Added "m" to all dimensions					Drawing #: <b>1-107</b>
3	04/05/20	Changed Font Size					
2	27/02/20	Changed Text & Dim.					
1	11/19/18	ADDITIONAL NOTES					
NO.	DATE	REVISION	Scale: <b>N.T.S.</b>				



**NOTES:**

1. ALL BACK SLOPES 4:1 UNLESS NOTED OTHERWISE.
2. SLOPES STEEPER THAN 4:1 REQUIRE 1m SHOULDER WIDENING & GUARD RAIL INSTALLATION.
3. PAVEMENT STRUCTURES AS PER DESIGN STANDARDS SECTION 3.5.
4. EROSION CONTROL MEASURES TO BE INSTALLED WITHIN SIDE SLOPES AND BOTTOM OF DITCH AS REQUIRED
5. MINIMUM CROSSFALL 2.5%, MAXIMUM CROSSFALL 4.0%

8		
7		
6		
5		
4	22/06/20	Revised Note 5
3	27/02/20	Revised Text
2	11/19/18	Revised Notes
1	4/14/16	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: N / A

**TYPICAL CROSS SECTION  
RURAL ROADS**


Scale: N.T.S.

Date: Feb. 22, 2011


Drawing #: 1-200



**APPROACH PLAN**



**DITCH AND CULVERT LOCATION**



**APPROACH CROSS SECTION**

**NOTES:**

1. WHEN CULVERTS ARE REQUIRED, THEY MUST BE CORRUGATED STEEL PIPE CULVERTS AND BE THE FOLLOWING MIN. DIAMETERS:  
 RESIDENTIAL - 0.40m  
 INDUSTRIAL - 0.50m  
 - LENGTH WILL VARY WITH DEPTH OF FILL (MIN. 10.0m)  
 - CULVERT TO BE PLACED AT TOE OF BACKSLOPE  
 - MINIMUM DEPTH OF COVER 0.5m
2. MIN. APPROACH LENGTH MEASURED FROM EDGE OF ROAD SHOULDER TO R/W BOUNDARY.

8		
7		
6		
5		
4		
3		
2	11/19/18	Revised Drawings
1	4/14/16	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: L. LEEPER

**INDUSTRIAL / COMMERCIAL APPROACHES (RURAL)**

Date: Feb. 22, 2011




Drawing #: 1-201

Scale: N.T.S.




**NOTES:**

1. WATERMAIN AND HYDRANT AND/OR STORM SEWER MAY BE LOCATED ON EITHER SIDE OF ROAD.
2. UNDERGROUND POWER AND STREET LIGHTS TO BE ON THE OPPOSITE SIDE TO WATERMAIN.
3. LUMINARE SUPPORTS TO BE OF THE FRANGIBLE BASE, SLIP BASE, OR FRANGIBLE COUPLING TYPE.
4. ALL BACK SLOPES 4:1 UNLESS NOTED OTHERWISE.
5. PAVEMENT STRUCTURES AS PER DESIGN STANDARDS SECTION 3.5.
6. HYDRANTS TO BE LOCATED IN WIDENING AS PER DWG. 1-203
7. EROSION CONTROL MEASURES TO BE INSTALLED WITHIN SIDE SLOPES AND BOTTOM OF DITCH AS REQUIRED
8. MINIMUM CROSSFALL 2.5%, MAXIMUM 4.0%




8			<b>The City of Lloydminster</b>	Checked by: 	Approved by: 	Drawn by:	N / A		
7				<b>TYPICAL RURAL UTILITY LAYOUT</b>		Date:	Feb. 22, 2011		
6				<b>LAYOUT</b>		Drawing #:	1-202		
5	04/05/20	Revised Min/Max Case				Scale:	N.T.S.		
4	27/02/20	Revised Text							
3	11/20/18	Revised Notes							
2	4/14/16	Revised Notes							
1	15/05/12	Water and Sanitary Relocation							
NO.	DATE	REVISION							






**NOTES:**


1. BOLLARDS TO BE CONSTRUCTED AS PER DWG 1-204.

8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: <b>L. LEEPER</b>
5				<b>TYPICAL RURAL HYDRANT SHOULDER WIDENING LAYOUT</b>	Date: <b>Feb. 22, 2011</b>	
4	04/05/20	Moved Valve Location	Scale: <b>N.T.S.</b>		Drawing #: <b>1-203</b>	
3	27/02/20	Changed Notes				
2	20/11/18	Changed Notes				
1	15/05/12	Water and Sanitary Relocation				
NO.	DATE	REVISION				



300mm DIA. AUGER HOLE

TOP



ELEVATION

8		
7		
6		
5		
4		
3		
2	27/02/20	Changed Drawing Text
1	01/02/19	Changed Drawing Text
NO.	DATE	REVISION

**The City of Lloydminster**




Scale:  
N.T.S.


Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: A. Edwards

**150mm STEEL  
ROADWAY BOLLARD**


Date: Nov 23, 2016  
Drawing #: 1-204



TYPICAL "ZEBRA" CROSSWALK MARKINGS AT MIDBLOCK LOCATIONS AND RIGHT TURN CUT-OFFS



INTERSECTION LOCATIONS



LANE LINES

NOTES:

1. TO BE PLACED IN ACCORDANCE WITH THE "UNIFORM TRAFFIC CONTROL DEVICES" MANUAL.
2. LANE DIMENSIONS ARE FROM FACE OF CURB TO CENTRE OF LINE OR CENTRE OF LINE TO CENTRE OF LINE.

8		
7		
6		
5		
4		
3		
2	04/05/20	Revised Font Size
1	27/02/20	Revised Text
NO.	DATE	REVISION

The City of Lloydminster



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: N/A

PAVEMENT MARKINGS


Scale: N.T.S.

Date: Feb. 22, 2011


Drawing #: 1-300




RURAL / INDUSTRIAL




ARTERIAL ROADWAY




MEDIAN / CONCRETE DETAIL



INTERSECTION DETAIL






MATERIALS DETAIL  
ROUND POLE




MATERIALS DETAIL  
U-CHANNEL


**NOTE:**

1. SIGNS MOUNTED ON U-CHANNEL POLES EXCEPT WHEN INSTALLED IN CONCRETE.

8			<b>The City of Lloydminster</b>				
7				Checked by: 	Approved by: 	Drawn by: <b>L. LEEPER</b>	
6				<b>TRAFFIC SIGNAGE</b>			
5	29/06/20	Changed Materials Details					Date: <b>Feb. 22, 2011</b>
4	23/06/20	Changed Pipe Dia.					Drawing #: <b>1-301</b>
3	27/02/20	Changed Notes					
2	03/21/18	Revised U-channel note.					
1	08/04/14	Added U-channel note.					
NO.	DATE	REVISION	Scale: <b>N.T.S.</b>				




MOUNT STREET IDENTIFICATION SIGNS AT 90 DEGREE ANGLES ON TOP OF EACH OTHER. ID SIGNS TO HAVE 100mm LETTERS ON COLLECTOR AND RESIDENTIAL STREETS AND 150mm LETTERS ABUTTING ARTERIAL ROADWAYS.




WHENEVER POSSIBLE, MOUNT SIGNS ON EXISTING LIGHT POSTS.

LOCAL RESIDENTIAL STREET






LOCAL RESIDENTIAL STREET




COLLECTOR STREET


**NOTES:**

1. WHERE PRACTICAL, MOUNT STREET NAME SIGNS:
  - ON A STREET LIGHT STANDARD AT THE INTERSECTION
  - ON THE TOP OF A YIELD OR STOP SIGN POST AT THE INTERSECTION
  - ON A SEPARATE POST ONLY IF THE ABOVE 2 LOCATIONS ARE NOT SUITABLE.
2. SIGNS MOUNTED ON U-CHANNEL POLES EXCEPT WHEN COUPLER IS REQUIRED.




8			 <p><b>The City of Lloydminster</b></p>	Checked by: 	Approved by: 	Drawn by: L. LEEPER	
7				<p><b>TRAFFIC SIGNAGE</b></p>			Date: Feb. 22, 2011
6							Drawing #: 1-302
5							
4							
3							
2	27/02/20	Revised Notes		Scale: N.T.S.			
1	08/04/14	Added U-channel note.					
NO.	DATE	REVISION					




TYPICAL PAVEMENT ARROWS




DETAIL OF APPROACH PAVEMENT MARKINGS

8				<b>The City of Lloydminster</b>				
7						Checked by: 	Approved by: 	Drawn by: A. EDWARDS
6				<b>HAND APPLIED MARKINGS</b>			Date: Jan 13, 2017	
5							Scale: N.T.S.	Drawing #: 1-303
4								
3								
2	04/05/20	Revised Font Size						
1	27/02/20	Revised Text						
NO.	DATE	REVISION						






GUTTER MILLING




BUTT JOINT MILLING

**NOTES:**




1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED.
2. LIMITS OF MILLING TO BE CONFIRMED BY ENGINEER.
3. TO BE USED FOR MILL AND OVERLAY OPERATIONS, AND WHEN FILLETS ARE USED IN DEFERRED SECOND LIFT PAVING.

8				<b>The City of Lloydminster</b>		
7				Checked by: 	Approved by: 	Drawn by: A. EDWARDS
6				<b>GUTTER AND BUTT JOINT MILLING</b>		
5						
4						
3	04/05/20	Revised Font Height				
2	27/02/20	Revised Dimensions		Scale: N.T.S.	Date: Jan 13, 2017	
1	21/03/18	Revised Notes			Drawing #: 1-400	
NO.	DATE	REVISION				




**NOTES:**

1. INSCRIBED CIRCLE TO BE CONCRETE, RED IN COLOUR
2. ONLY PLANTING SPECIES APPROVED BY THE CITY TO BE USED IN INNER LANDSCAPE ZONE
3. LANDSCAPING FEATURES MUST NOT INTERFERE WITH ACCESS TO, OR IMPEDE MAINTENANCE ON UTILITIES PASSING THROUGH ROUNDABOUT.
4. THE USE OF GRAVEL AND PUBLIC FURNITURE AS LANDSCAPING FEATURES TO BE AVOIDED.

8				<b>The City of Lloydminster</b>		
7				Checked by: 	Approved by: 	Drawn by: J. IDIOH
6				<b>ROUNDABOUT CROSS-SECTION</b>		
5						
4						
3						
2						
1	03/03/20	Edited Text		Scale: N.T.S.	Date: Jan. 11, 2019	Drawing #: 1-500
NO.	DATE	REVISION				





**NOTES:**

1. TRUCK APRON TO BE CONCRETE, RED IN COLOUR.
2. ONLY PLANTING SPECIES APPROVED BY THE CITY TO BE USED IN INNER LANDSCAPE ZONE.
3. PERIMETER LANDSCAPE ZONE TO CONTAIN NO PLANTINGS.
4. LANDSCAPING FEATURES MUST NOT INTERFERE WITH ACCESS TO, OR IMPEDE MAINTENANCE ON UTILITIES PASSING THROUGH ROUNDABOUT.
5. THE USE OF GRAVEL AND PUBLIC FURNITURE AS LANDSCAPING FEATURES TO BE AVOIDED.
6. SPLITTER ISLAND TO BE FILLED WITH CONCRETE, WHICH MAY BE STAMPED OR COLOURED FOR AESTHETICS.
7. PAVEMENT MARKINGS TO BE REVIEWED BY THE CITY OF LLOYDMINSTER.

8		
7		
6		
5		
4		
3		
2	23/06/20	Revised Note 7
1	03/03/20	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**





Scale: N.T.S.

Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: J. IDIOH

**ROUNDABOUT PLAN VIEW AND LANDSCAPING ZONES**



Date: Jan. 14, 2019  
Drawing #: 1-501



**NOTES:**




1. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.
2. CURB RETURNS REQUIRED AT ALL CROSSINGS
3. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF CURB AND PROVIDE POSITIVE DRAINAGE OVER THE TOP OF CURB.
4. 10M REBAR 6.0m LONG TO BE INSTALLED WHEN
5. REPLACING CURB & GUTTER OVER SERVICE CONNECTION AND HYDRANT LEAD TRENCHES.
6. 10M REBAR TO BE INSTALLED AT ALL LANE AND COMMERCIAL CROSSINGS.
7. REDUCE CURB HEIGHT AT ALL CROSSINGS.
8. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.


8			<b>The City of Lloydminster</b>				
7							
6	04/05/20	Revised Details		Checked by:	Approved by:	Drawn by:	
5	03/03/20	Revised Notes		<i>[Signature]</i>	<i>[Signature]</i>	N / A	
4	21/03/18	Revised Details					
3	04/14/16	Revised Notes					
2	10/12/13	Updated concrete notes					
1	21/03/13	Updated concrete type					
NO.	DATE	REVISION		Scale:	<b>STANDARD 150mm CURB WITH 250mm GUTTER</b>		Date:
			N.T.S.			Feb. 22, 2011	
						Drawing #:	
						<b>2-100</b>	



**NOTES:**

1. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.
2. CURB RETURNS REQUIRED AT ALL CROSSINGS
3. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF CURB AND PROVIDE POSITIVE DRAINAGE OVER THE TOP OF CURB.
4. 10M REBAR 6.0m LONG TO BE INSTALLED WHEN REPLACING CURB & GUTTER OVER SERVICE CONNECTION AND HYDRANT LEAD TRENCHES.
5. 10M REBAR TO BE INSTALLED AT ALL LANE AND COMMERCIAL CROSSINGS.
6. REDUCE CURB HEIGHT AT ALL CROSSINGS.
7. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.

8			<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: N / A
6	04/05/20	Revised Details		<b>STANDARD 200mm CURB WITH 250mm GUTTER</b>		
5	03/03/20	Revised Notes				
4	22/03/18	Changed Curb Dimensions				
3	14/04/16	Revised Notes				
2	10/12/13	Updated concrete notes				
1	21/03/13	Updated concrete type				
NO.	DATE	REVISION				



**NOTES:**

1. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.
2. CURB RETURNS REQUIRED AT ALL CROSSINGS
3. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF CURB AND PROVIDE POSITIVE DRAINAGE OVER THE TOP OF CURB.
4. 10M REBAR 6.0m LONG TO BE INSTALLED WHEN

5. REPLACING CURB & GUTTER OVER SERVICE CONNECTION AND HYDRANT LEAD TRENCHES.
6. 10M REBAR TO BE INSTALLED AT ALL LANE AND COMMERCIAL CROSSINGS.
7. REDUCE CURB HEIGHT AT ALL CROSSINGS.
8. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.

8		
7		
6	04/05/20	Removed "mm" From Dims.
5	03/03/20	Revised Notes & Detail
4	22/03/18	Revised Notes
3	14/04/16	Revised Notes
2	10/12/13	Updated concrete notes
1	21/03/13	Updated concrete type
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: N/A

**ROLLED FACE CURB AND GUTTER**




Date: Feb. 22, 2011


Drawing #: 2-102



**NOTES:**




1. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.
2. CURB RETURNS REQUIRED AT ALL CROSSINGS.
3. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF CURB AND PROVIDE POSITIVE DRAINAGE OVER THE TOP OF CURB.
4. 10M REBAR 6.0m LONG TO BE INSTALLED WHEN REPLACING CURB & GUTTER OVER SERVICE CONNECTION AND HYDRANT LEAD TRENCHES.
5. 10M REBAR TO BE INSTALLED AT ALL LANE AND COMMERCIAL CROSSINGS.
6. REDUCE CURB HEIGHT AT ALL CROSSINGS.
7. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.

8			<b>The City of Lloydminster</b>			
7						
6						
5	04/05/20	Removed "mm" from Dims.		Checked by: 	Approved by: 	Drawn by: N/A
4	13/08/18	Revised Notes				
3	14/04/16	Revised Notes				
2	10/12/13	Updated concrete notes				
1	20/03/13	Updated concrete type				
NO.	DATE	REVISION				
			Scale: N.T.S.	<b>STANDARD BARRIER CURB</b>		Date: Feb. 22, 2011
					Drawing #: 2-103	





**NOTES:**

1. CONTRACTION JOINTS 50mm.DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.
2. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.

8			<b>The City of Lloydminster</b>			
7						
6						
5	22/06/20	Revised Note 1		Checked by: 	Approved by: 	Drawn by: L. LEEPER
4	03/04/20	Revised Notes				
3	13/08/18	Revised Notes				
2	14/04/16	Revised Notes				
1	10/12/13	Revised Notes				
	NO.	DATE		REVISION	<b>PINNED CURB MEDIAN DETAIL</b>	
			Scale: N.T.S.			Drawing #: 2-104





**NOTES:**

1. 10M REBAR 6.0m LONG TO BE INSTALLED WHEN REPLACING CURB & GUTTER OVER SERVICE CONNECTION AND HYDRANT LEAD TRENCHES.
2. ALL LANE OR COMMERCIAL CROSSINGS SHALL BE AS PER DWG. 2-109.
3. REDUCE CURB HEIGHT AT ALL CROSSINGS AS PER DWG. 2-109.
4. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.
5. 150mm MINIMUM COMPACTED GRANULAR SUBBASE.
6. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.
7. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF WALK AND PROVIDE POSITIVE DRAINAGE OVER TOP OF WALK.

8		
7		
6		
5	22/06/20	Revised Details
4	03/04/20	Revised Details & Notes
3	22/03/18	Revised Notes
2	14/04/16	Revised Notes
1	10/12/13	Revised Concrete Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*

Approved by: *[Signature]*



Drawn by: N/A

**STRAIGHT FACE CURB, GUTTER AND MONOLITHIC SIDEWALK**


Date: Feb. 22, 2011

Drawing #: 2-106





PLAN



CONNECTION JOINT DETAIL

**NOTES:**

1. SIDEWALK IS 180mm THICK IN COMMERCIAL / INDUSTRIAL AREAS.
2. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.
3. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF WALK AND PROVIDE POSITIVE DRAINAGE OVER THE TOP OF WALK.
4. 10M REBAR 6.0m LONG TO BE INSTALLED WHEN REPLACING WALK OVER SERVICE CONNECTION AND HYDRANT LEAD TRENCHES.
5. 10M REBAR TO BE INSTALLED AT ALL LANE AND COMMERCIAL CROSSINGS.
6. WHEN CONNECTING TO EXISTING WALK, SAW CUT EDGE AND INSTALL THREE 10M DOWELS @ 350 O.C.

8		
7		
6	04/05/20	Removed "mm" from Dims.
5	14/08/18	Revised Notes
4	22/03/18	Revised Notes
3	14/04/18	Revised Notes
2	10/12/13	Changed concrete notes
1	21/03/13	Changed concrete type
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: N/A

**1.5m SEPARATE SIDEWALK**

Date: Feb. 22, 2011

Drawing #: 2-107



**NOTES:**

1. NORMAL CROSS-FALL ON SERVICE STRIP IS 2.0% TOWARDS ROAD. ACTUAL CROSS-FALL WILL VARY AND IN SOME CASES SLOPE WILL BE AWAY FROM ROAD. CONFIRM CROSS-FALL REQUIREMENTS ON-SITE WITH ENGINEER.
2. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS OR AS DIRECTED BY ENGINEER.
3. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.

8		
7		
6		
5	04/05/20	Darkened a Line
4	03/04/20	Revised Detail
3	22/11/16	Additional Sand Detail
2	15/04/16	Removed Edger Detail
1	10/12/13	Changed Concrete Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*




Approved by: *[Signature]*

Drawn by: N/A


**MONO SERVICE STRIP AND CONCRETE EDGER**

Date: Feb. 22, 2011

Drawing #: 2-108



SECTION A-A STRAIGHT FACE



SECTION A-A ROLLED FACE

**NOTES:**

1. MAXIMUM ALLOWABLE 'X' AS PER ENGINEER.
2. CONCRETE STRENGTH TO BE TYPE HS, 32MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5-8% AIR ENTRAINMENT.
3. SIDEWALK THICKNESS = 120mm AT RESIDENTIAL CROSSINGS, 180mm AT ALL OTHER CROSSINGS.
4. CURB AND GUTTER SECTION REQUIRES REBAR. REFER TO DWGS 2-105 & 2-106.

9	09/09/20	Labelled contraction joints
8	04/05/20	Removed "mm" From Dims.
7	04/03/20	Revised Details
6	14/08/18	Additional Notes
5	22/03/18	Additional Notes
4	22/11/16	Additional Notes
3	14/04/16	Revised Notes
2	10/12/13	Revised concrete notes
NO.	DATE	REVISION

**The City of Lloydminster**






Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: N / A

**COMMERCIAL / LANE CROSSING  
MONOLITHIC SIDEWALK**

Date: Feb. 22, 2011  
Drawing #: 2-109

Scale: N.T.S.



**NOTES:**

1. MAXIMUM ALLOWABLE 'X' AS PER ENGINEER.
2. CONCRETE STRENGTH TO BE TYPE HS, 32MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5-8% AIR ENTRAINMENT.
3. SIDEWALK THICKNESS = 120mm AT RESIDENTIAL CROSSINGS, 180mm AT ALL OTHER CROSSINGS.
4. CURB AND GUTTER SECTION REQUIRES REBAR. REFER TO DWGS 2-100 & 2-101.

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: **L. LEEPER**




**COMMERCIAL / LANE CROSSING  
SEPARATE SIDEWALK**

Date: **Feb. 22, 2011**

Drawing #: **2-110**

Scale: **N.T.S.**

9	21/09/20	Labelled contraction joints
8	05/03/20	Revised Details
7	14/08/18	Revised Details
6	22/03/18	Revised Details
5	03/06/17	Revised Taper
4	22/11/16	Additional Notes
3	14/04/16	Revised Notes
2	10/12/13	Updated concrete notes
NO.	DATE	REVISION



**SECTION A-A STRAIGHT FACE**

- NOTES:**
1. MAXIMUM ALLOWABLE 'X' AS PER ENGINEER.
  2. CONCRETE STRENGTH TO BE TYPE HS, 32MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5-8% AIR ENTRAINMENT.
  3. SIDEWALK THICKNESS = 120mm AT RESIDENTIAL CROSSINGS, 180mm AT ALL OTHER CROSSINGS.
  4. CURB AND GUTTER SECTION REQUIRES REBAR. REFER TO DWGS 2-105 & 2-106.

8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
**N.T.S.**

Checked by: *[Signature]*




Approved by: *[Signature]*

Drawn by: **N/A**

Date:  
**Sept. 21, 2020**

Drawing #:  
**2-111**

**RESIDENTIAL APRON CROSSING  
MONOLITHIC SIDEWALK**



**NOTES:**

1. MAXIMUM ALLOWABLE 'X' AS PER ENGINEER.
2. CONCRETE STRENGTH TO BE TYPE HS, 32MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5-8% AIR ENTRAINMENT.
3. SIDEWALK THICKNESS = 120mm AT RESIDENTIAL CROSSINGS.
4. CURB AND GUTTER SECTION REQUIRES REBAR. REFER TO DWGS 2-100 & 2-101.

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: L. LEEPER


**RESIDENTIAL APRON CROSSING  
SEPARATE SIDEWALK**

Date: Feb. 22, 2011

Drawing #: 2-112


Scale: N.T.S.

8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION



GRATE TOP VIEW

GRATE END VIEW




CROSS SECTIONAL VIEW

**NOTES:**

1. ACO DRAIN LINE 100 OR APPROVED EQUIVALENT
2. FINISHED CONCRETE SURROUND TO BE 3mm ABOVE GRATE
3. T = Min. 100mm
4. EXPANSION JOINT PLACED ON BOTH SIDES IS PREFERRED, MONOLITHIC POUR IS ACCEPTABLE

8		
7		
6		
5		
4	21/09/20	Changed Dwg No. from 2-111
3	22/06/20	Underlined Detail Name
2	04/05/20	Revised Font Size
1	20/11/18	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

**TRENCH DRAIN**


Drawn by:  
**A. EDWARDS**

Date:  
**Jan 13, 2017**


Drawing #:  
**2-113**




TYPE A




TYPE B-1 (BOULEVARD > 2.0m)




TYPE B-2 (BOULEVARD < 2.0m)



TYPE C



TYPICAL CROSS SECTION A-A



TYPE D

- A) MATCH ASPHALT SURFACE TO GUTTER LIP WITHIN 3mm.
- B) IF ASPHALT TOPLIFT IS DEFERRED, PLACE ASPHALT RAMP FOR THE WIDTH OF CURB RAMP, AND EXTENDING MINIMUM 1.0m INTO ROAD

**NOTES:**

1. TOOLED GROOVES 5mm WIDE X 10mm DEEP, BROOM FINISH. GROOVE SPACING 150mm O.C. ADJACENT TO CURB.
2. GROOVES TO BE IN DIRECTION OF TRAVEL.
3. WHEN REQUIRED, TRANSITION FROM STRAIGHT FACE CURB TO ROLLED FACE CURB AT CURB RAMP.
4. CURBS AND RAMP TO BE POURED MONOLITHICALLY.
5. WIDTH OF RAMP MUST EQUAL WIDTH OF WALK (MIN. 1.5m, MAX. 3.0m) EXCEPT "TYPE A".
6. MAXIMUM SLOPE ON CURB RAMP TO BE 8%.
7. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF WALK AND PROVIDE POSITIVE DRAINAGE OVER THE TOP OF WALK.

8		
7		
6	20/10/20	Removed Type A2, Added B2
5	01/02/19	Added Grass Hatch
4	22/03/18	Added Note
3	06/03/17	Revised Taper
2	22/11/16	Additional Dimensions
1	04/07/16	Removed widening in Type C
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: N / A



**CURB RAMP**

Scale: N.T.S.

Date: Feb. 22, 2011




Drawing #: 2-200







**NOTES:**

1. TYPICAL CURB AND GUTTER TREATMENT AT CATCH BASINS WHEN ASPHALT TOP LIFT IS DEFERRED.
2. DROPPED GUTTER SECTION TO BE REMOVED AND REPLACED PRIOR TO TOP LIFT BEING PLACED. REMOVAL NOT REQUIRED WHERE FILLET CONSTRUCTION OF BOTTOM LIFT IS USED.


8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: L. LEEPER
5				<b>TYPICAL DROPPED GUTTER LIP FOR TWO STAGE PAVING</b>	Date: Feb. 22, 2011	
4	05/03/20	Revised Notes & Details			Drawing #: 2-201	
3	01/21/19	Changed Drawing Views				
2	11/20/18	Revised Notes				
1	4/14/16	Revised Notes				
NO.	DATE	REVISION	Scale: N.T.S.			



**PLAN - F-51 SIDE INLET, FRAME AND COVER SET IN  
150mm CURB WITH 250mm GUTTER**



**SECTION A-A**



**SECTION B-B**

**NOTES:**

1. TYPICAL CURB AND GUTTER TREATMENT AT CATCH BASINS WHEN ASPHALT TOP LIFT IS DEFERRED.
2. DROPPED GUTTER SECTION TO BE REMOVED AND REPLACED PRIOR TO TOP LIFT BEING PLACED. REMOVAL NOT REQUIRED WHERE FILLET CONSTRUCTION OF BOTTOM LIFT IS USED.

8		
7		
6		
5		
4		
3	05/03/20	Changed Dwg, Added Notes
2	02/01/19	Modified Drawing
1	23/03/18	Removed 500mm Gutter
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*



Approved by: *[Signature]*

Drawn by: L. LEEPER


**TYPE F-51 CATCH BASIN  
CURB FINISHING DETAIL**

Date: Feb. 22, 2011


Drawing #: 2-202



SECTION A-A



SECTION B-B  
Full Curb



SECTION B-B  
Pinned Median

NOTES:

1. CONTRACTION JOINTS AT 3m INTERVALS.
2. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.

8		
7		
6		
5		
4	04/05/20	Rev. Font Size, Removed "mm"
3	05/03/20	Revised Notes & Updated Drawings
2	11/23/18	Revised Notes & Updated Drawings
1	4/14/16	Revised Notes
NO.	DATE	REVISION

The City of Lloydminster



Checked by: *[Signature]*

Approved by: *[Signature]*



Drawn by: N/A

TYPICAL MEDIAN


Scale: N.T.S.

Date: Feb. 22, 2011

Drawing #: 2-203







SERVICE BOX CAP



**NOTES:**




1. AT THE TIME OF SIDEWALK / CURB CONSTRUCTION AN IMPRESSION OF A SERVICE BOX CAP OR THE LETTERS "CC" SHALL BE NEATLY MARKED INTO THE MOIST CONCRETE DIRECTLY OPPOSITE EACH SERVICE BOX.
2. IF MISSED, OR IF A NEW CC IS INSTALLED IN AN EXISTING AREA WITHOUT DISTURBING THE SIDEWALK, GRIND THE LETTERS "CC" INTO THE SURFACE.


8				<b>The City of Lloydminster</b>		
7				Checked by: 	Approved by: 	Drawn by: L. LEEPER
6				<b>"CC" STAMP</b>		
5						
4						
3						
2	05/03/20	Additional Notes		Scale: N.T.S.	Date: Feb. 22, 2011	
1	22/11/16	Additional Notes			Drawing #: <b>2-204</b>	
NO.	DATE	REVISION				




**NOTES:**

1. CENTERLINE OF SWALE TO MATCH GUTTER ELEVATION AT UPSTREAM END. LOWER GUTTER LIP TO MEET CENTERLINE OF SWALE.
2. SWALE EDGE TO MATCH GUTTER ELEVATION ON DOWNSTREAM END. LOWER GUTTER LIP TO MATCH CENTERLINE OF SWALE.
3. EXPANSION JOINTS TO BE CONSTRUCTED AT ENDS OF SWALE WHERE SWALE ABUTS GUTTERS.
4. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.
5. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT


8			<b>The City of Lloydminster</b>		Checked by: 	Approved by: 	Drawn by: A. EDWARDS
7					<b>CONCRETE DRAINAGE SWALE (ROADWAY)</b>	Date: July 25, 2017	
6						Drawing #: 2-205	
5							
4	04/05/20	Darkened Line, Rem. "mm"					
3	06/03/20	Revised Notes					
2	23/03/18	Revised Dimensions					
1	22/11/16	Revised Line Width					
NO.	DATE	REVISION	Scale: N.T.S.				



**SECTION B-B**



20mm ALUMINUM FORGED  
MANHOLE STEPS OR AS  
PER MANUFACTURER  
SPECIFICATION



**SECTION A-A**

**NOTES:**

1. PRECAST RINGS, CONES AND BARRELS TO MEET CURRENT ASTM C478 STANDARDS.
2. SPECIAL BASE DESIGN REQUIRED FOR DEPTHS OVER 9.0m.
3. CHANNELLING AND BENCHING TO BE FINISHED TO TROWEL SMOOTHNESS. CONTINUE MAIN PIPE WHERE POSSIBLE.
4. CONICAL TOP TO BE USED WHERE DISTANCE FROM BENCH TO MANHOLE COVER EXCEEDS 2.0m.
5. INSTALL SAFETY PLATFORMS FOR ALL MANHOLES OVER 5.0m DEEP. LOCATE 2m ABOVE PIPE AS PER STANDARD DRAWING 3-201.
6. MANHOLE FRAME AND COVER TO BE AS PER STANDARD DRAWING 3-202.
7. BENCHING CONCRETE SHALL BE A MINIMUM OF 32MPa COMPRESSIVE STRENGTH, TYPE HS.
8. BUOYANCY CALCULATIONS TO BE PROVIDED TO THE CITY FOR ALL MANHOLES THAT HAVE HALF OR MORE OF VERTICAL DEPTH BELOW THE SURROUNDING WATER TABLE ELEVATION.

8		
7	06/03/20	Added Note 8
6	23/03/18	Revised Details
5	14/04/16	Revised Notes
4	08/04/14	Changed grade ring thickness
3	10/12/13	Updated concrete notes
2	21/03/13	Updated concrete type
1	22/06/11	Detail reference, Note 6.
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*




Approved by: *[Signature]*

Drawn by: L. LEEPER

**PRECAST MANHOLE FOR PIPES  
UP TO 525mm DIAMETER**

Date: Feb. 22, 2011

Drawing #: 3-100



**NOTES:**

1. PRECAST RINGS, CONES AND BARRELS TO MEET CURRENT ASTM C478 STANDARDS.
2. SPECIAL BASE DESIGN REQUIRED FOR DEPTHS OVER 9.0m.
3. CHANNELLING AND BENCHING TO BE FINISHED TO TROWEL SMOOTHNESS. CONTINUE MAIN PIPE WHERE POSSIBLE.
4. CONICAL TOP TO BE USED WHERE DISTANCE FROM BENCH TO MANHOLE COVER EXCEEDS 2.0m.
5. INSTALL SAFETY PLATFORMS FOR ALL MANHOLES OVER 5.0m DEEP. LOCATE 2m ABOVE PIPE AS PER STANDARD DRAWING 3-201.
6. MANHOLE FRAME AND COVER TO BE AS PER STANDARD DRAWING 3-202.
7. BENCHING CONCRETE SHALL BE A MINIMUM OF 32MPa COMPRESSIVE STRENGTH, TYPE HS.
8. BUOYANCY CALCULATIONS TO BE PROVIDED TO THE CITY FOR ALL MANHOLES THAT HAVE HALF OR MORE OF VERTICAL DEPTH BELOW THE SURROUNDING WATER TABLE ELEVATION.

9		
8	06/03/20	Added Note 8
7	16/08/18	Added surface flush with rim
5	14/04/16	Revised Notes
4	08/04/14	Changed grade ring thickness
3	10/12/13	Updated concrete notes
2	21/03/13	Updated concrete type
1	22/06/11	Detail reference, Note 6.
NO.	DATE	REVISION

**The City of Lloydminster**




Scale: N.T.S.

Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: L. LEEPER

**PRECAST MANHOLE FOR PIPES  
600mm TO 900mm DIAMETER**

Date: Feb. 22, 2011  
Drawing #: 3-101



**NOTES:**

1. PRECAST RINGS, CONES AND BARRELS TO MEET CURRENT A.S.T.M. C478 STANDARDS.
2. CHANNELLING AND BENCHING TO BE FINISHED TO TROWEL SMOOTHNESS. CONTINUE MAIN PIPE WHERE POSSIBLE.
3. CONICAL TOP TO BE USED WHERE DISTANCE FROM BENCH TO MANHOLE COVER EXCEEDS 2.0m.
4. INSTALL SAFETY PLATFORMS FOR ALL MANHOLES OVER 5.0m DEEP. LOCATE 2m ABOVE PIPE AS PER STANDARD DRAWING 3-201.
5. MANHOLE FRAME AND COVER TO BE AS PER STANDARD DRAWING 3-202.
6. BENCHING CONCRETE SHALL BE A MINIMUM OF 32MPa COMPRESSIVE STRENGTH, TYPE HS.
7.  $D \Rightarrow 1050\text{mm}$ .
8. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED.
9. BUOYANCY CALCULATIONS TO BE PROVIDED TO THE CITY FOR ALL MANHOLES THAT HAVE HALF OR MORE OF VERTICAL DEPTH BELOW THE SURROUNDING WATER TABLE ELEVATION.

9	04/05/20	Changed Font Ht., Rem. "mm"
8	06/03/20	Added Note 9
7	02/07/19	Revised Notes
6	16/08/18	Revised Notes & Specs.
5	14/04/16	Revised Notes
4	08/04/14	Changed grade ring thickness
3	10/12/13	Updated concrete notes
2	21/03/13	Updated concrete type
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.


Checked by:	Approved by:	Drawn by: N/A
-------------	--------------	---------------

**TYPICAL T-RISER MANHOLE FOR PIPES 1050mm DIAMETER AND LARGER**

Date: Feb. 22, 2011
Drawing #: 3-102








**NOTES:**

1. PRECAST RINGS, CONES AND BARRELS TO MEET CURRENT A.S.T.M. C478 STANDARDS.
2. CAST IN PLACE CONCRETE TO BE TYPE HS, 32MPa AT 28 DAYS.
3. COMPACT FILL AROUND MANHOLES TO A MINIMUM OF 98% STANDARD PROCTOR DENSITY.
4. CONICAL TOP TO BE USED WHERE DISTANCE FROM TOP OF PIPE TO MANHOLE COVER EXCEEDS 2.0m.
5. VERTICAL SIDE OF CONICAL MANHOLE ON UPSTREAM SIDE.
6. INSTALL SAFETY PLATFORMS FOR ALL MANHOLES OVER 5.0m DEEP. LOCATE 2.0m ABOVE PIPE AS PER STANDARD DRAWING 3-201.
7. MANHOLE FRAME AND COVER TO BE AS PER STANDARD DRAWING 3-202.
8. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED.

8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: L. LEEPER


**PERCHED MANHOLE**

Date: July 2, 2019

Drawing #: 3-104

Scale: N.T.S.

MINIMUM DISTANCE BETWEEN PIPE OPENINGS, 225 mm OR 1/2 LARGER PIPE OD, WHICHEVER IS GREATER



**NOTES:**

1. MANHOLES MUST BE LARGE ENOUGH TO ACCOMMODATE THE MAXIMUM INTERSECTING PIPE SIZE.
2. THE MINIMUM DISTANCE BETWEEN OPENINGS FOR PIPES SHALL BE 225 mm OR 1/2 OF THE LARGER PIPE'S OUTER DIAMETER (OD), WHICHEVER IS GREATER.
3. MANHOLES SHALL BE DESIGNED WITH SUFFICIENT INSIDE DIMENSIONS TO PERFORM INSPECTION AND CLEANING OPERATIONS, ALLOW FOR PROPER CHANNEL CONSTRUCTION WITHOUT DIFFICULTY AND MINIMIZE HYDRAULIC LOSSES THROUGH THE MANHOLE.
4. PRE-BENCHED MANHOLE BASES SHALL BE USED WHEREVER POSSIBLE WITH PRE-CORED CONNECTION HOLES AND WATER-TIGHT DURASEAL OR G-LOC JOINTS OR APPROVED EQUAL.
5. OPENINGS FOR CONNECTIONS MADE IN THE FIELD SHALL NOT BE GREATER THAN THE OUTER DIAMETER OF THE PIPE BY MORE THAN 50 mm IN ANY DIRECTION AND SHALL BE CORED OR CUT, AND THE OPENING AROUND THE PIPE SEALED WITH NON-SHRINK GROUT.
6. 1500 mm OR LARGER DIAMETER MANHOLES ARE REQUIRED WHEN CONNECTING SEWERS THAT ARE BETWEEN 600 mm AND 900 mm.

8		
7		
6		
5		
4		
3		
2	06/03/20	Renumbered DWG from 3-207
1	23/03/18	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: A. ADEBAYO

**MANHOLE PENETRATIONS AND DESIGN**

Scale: N.T.S.




Date: Apr. 05, 2016



Drawing #: 3-105



**NOTES:**

1. MANHOLES TO BE ADJUSTED TO FINISHED GRADE PRIOR TO PLACING ASPHALTIC CONCRETE SURFACE COURSE.
2. MANHOLE COLLARS TO BE SET IN MORTAR CONSISTING OF 3 PARTS SAND & 1 PART CEMENT. PARGING ON OUTSIDE OF MANHOLE COLLARS ONLY. INSIDE FACES SHALL BE POINTED SUCH THAT A NEAT, EVEN FINISH RESULTS.

8			<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: N/A
6				<b>NON-FLOATING MANHOLE FRAME ADJUSTMENT DETAIL</b>		
5			Scale: N.T.S.	Date: Feb. 22, 2011	<b>3-200</b>	
4	04/05/20	Removed "mm", "Max" to "MAX"				
3	16/08/18	Changed Dwg Title				
2	23/03/18	Changed Details				
1	08/04/14	Changed min grade rings				
NO.	DATE	REVISION				



**NOTES:**

1. PLATFORMS TO BE INSTALLED IN ALL MANHOLES OVER 5.0m IN DEPTH (RIM TO INVERT)

8		
7		
6		
5		
4	04/05/20	Rem. "mm", Adj. Font Ht.
3	01/03/19	Removed Features
2	8/16/18	Added Features
1	4/14/16	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**

*Planning & Engineering*



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: N / A

Scale: N.T.S.


**SAFETY PLATFORM**

Date: Feb. 22, 2011

Drawing #: 3-201



FRAME




SECTION A - A

NOTES:


1. CASTINGS SHALL BE TRUE TO PATTERN AND FREE FROM CRACKS, GAS HOLES, FLAWS, OR SHRINKAGE. BEARING SURFACE SHALL BE MACHINED TO PREVENT ROCKING.
2. USE FOR ALL ROADWAY, GRAVEL APPLICATIONS.
3. COVER TO BE AS PER STANDARD DRAWING 3-204 FOR SANITARY SEWER SYSTEM OR 3-205 FOR STORM SEWER SYSTEM.

8				<b>The City of Lloydminster</b>						
7				Checked by:	Approved by:	Drawn by:	L. LEEPER			
6				<b>F-80 MANHOLE FRAME</b>			Date:	Feb. 22, 2011		
5							Scale:	N.T.S.	Drawing #:	3-202
4										
3										
2										
1	4/14/16	Rev. Notes, Dwg. Title, Rem. Cover								
NO.	DATE	REVISION								






WHEN RESURFACING EXISTING ROADS, LOOSEN FRAME FROM ASPHALT. SPRAY FRAME AND COVER WITH OIL TO EASE REMOVAL OF NEW ASPHALT. AFTER PAVER HAS LAID OUT ASPHALT, REMOVE ALL ASPHALT FROM THE FRAME AND COVER.





DURING PAVING OPERATION



LIFT THE FRAME AND COVER AND USE ASPHALT THAT WAS REMOVED TO PACK UNDER FLANGE AND FEATHER OUT TO APPROX. 50 cm FROM EDGE OF FRAME. THE ROLLER CAN PRESS FRAME AND COVER TO A SMOOTH INSTALLATION. LIFT HOLES MUST BE CLEANED OUT BEFORE THE MANHOLE IS LEFT.

FINAL PLACEMENT AND COMPACTION

8				<b>The City of Lloydminster</b>	Checked by: 	Approved by: 	Drawn by: L. LEEPER				
7											
6											
5											
4											
3											
2	06/03/20	Added Detail Titles						Scale: N.T.S.	<b>F-80 MANHOLE ADJUSTMENT DETAIL</b>	Date: March 9, 2015	Drawing #: 3-203
1	14/04/16	Revised Notes									
NO.	DATE	REVISION									



SECTION A-A

**The City of Lloydminster**

8		
7		
6	06/03/20	Underlined Section Titles
5	03/12/18	Added Vent Holes
4	16/08/18	Revised Text's Font Height
3	23/03/18	Revised Text Height
2	22/11/16	Revised Dimensions
1	11/02/16	Revised Cover Text
NO.	DATE	REVISION



Scale:  
N.T.S.

Checked by: *[Signature]*






Approved by: *[Signature]*

Drawn by: L. LEEPER

**TF-80LSAN Sanitary Sewer Cover  
(City Logo)**

Date: Dec. 14, 2015  
Drawing #: 3-204





SECTION A-A

8		
7		
6		
5		
4	06/03/20	Underlined Section Text
3	23/03/18	Revised Text Height
2	22/11/16	Revised Dimensions
1	08/02/16	Revised Cover Text
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*



Approved by: *[Signature]*

Drawn by: L. LEEPER

**TF-80LSTM Storm Sewer Cover  
(City Logo)**

Date: Dec. 14, 2015




Drawing #: 3-205





SECTION A-A

**NOTES:**

1. USE ON SANITARY MANHOLES, LOCATED IN ROADWAY SAGS OR GRASSED AREAS WHERE THERE IS A RISK OF INFLOW.
2. INSTALLERS MUST HOLD A LIFESPAN INSTALLATION AND MAINTENANCE CERTIFICATE
3. ADJUST TAPERED ADJUSTMENT RISER(S) SO THAT FRAME IS ANGLED TO BE FLUSHED WITH THE PAVED SURFACE.

8				Checked by: 	Approved by: 	Drawn by: A. EDWARDS	
7				<b>WATERTIGHT MANHOLE COVER</b>			Date: April 19, 2016
6							Drawing #: 3-206
5							
4							
3	06/03/20	Underlined "Section A-A"					Scale: N.T.S.
2	16/08/18	Additional Notes					
1	22/11/16	Additional Notes					
NO.	DATE	REVISION					


PLAN




SECTION A-A

NOTES:

1. CASTINGS SHALL BE TRUE TO PATTERN AND FREE FROM CRACKS, GAS HOLES, FLAWS, OR SHRINKAGE. BEARING SURFACE SHALL BE MACHINED TO PREVENT ROCKING.
2. USE FOR STORM SEWER MANHOLES IN GRASSED AREAS.

8			<b>The City of Lloydminster</b>			
7				Checked by: <i>[Signature]</i>	Approved by: <i>[Signature]</i>	
6				Drawn by: <b>A. Edwards</b>		
5			<b>F-39 FRAME AND LOCKING COVER</b>	Date: <b>June 30, 2016</b>		
4				Drawing #: <b>3-208</b>		
3						
2						
1	20/08/2018	Revised Notes		Scale: <b>N.T.S.</b>		
NO.	DATE	REVISION				



X = LENGTH AND DIAMETER OF SERVICE CONNECTIONS TO BE INCLUDED IN EXFILTRATION TEST CALCULATION.

**NOTES:**

1. THE ENTIRE LENGTH OF SERVICE IS NOT INCLUDED. ONLY THE PORTION BELOW THE 1 METRE HEAD IS INCLUDED IN THE EXFILTRATION TEST
2. ALL DIMENSIONS ARE IN MILLIMETRES.

8		
7		
6		
5		
4		
3		
2		
1	06/03/20	REVISED TEXT
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: J. IDIOH

**TYPICAL PIPE SECTION EXFILTRATION TEST**

Date: AUG. 20, 2018

Drawing #: 3-300




Scale: N.T.S.





CLASS	USE	A			B		
		MATERIAL	MAX LIFT	% SPD	MATERIAL	MAX LIFT	% SPD
I	UNDER ROADS	IMPORTED GRANULAR	300	98	IMPORTED GRANULAR	150	100
II	UNDER ROADS	NATIVE	300	98	NATIVE	150	100
III	LANDSCAPED AREAS	NATIVE	300	95	NATIVE	200	95
IV	OPEN FIELD	NATIVE	300	95	NATIVE	300	95

**NOTES:**

- ALL TRENCHED WALLS SHALL BE SLOPED OR SHORED IN CONFORMANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY REGULATIONS CURRENTLY IN EFFECT.
- SURFACE DRAINAGE TO BE RECTIFIED FOR IMMEDIATE AREA IF CLASS IV BACKFILL IS USED.

8				<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: L. LEEPER	
6				<b>TRENCH BACKFILL</b>			Date: Feb. 22, 2011
5							Drawing #: 4-100
4	06/03/20	Notes Formatting					Scale: N.T.S.
3	21/12/16	Updated Notes					
2	30/06/16	Updated Notes					
1	08/04/14	Changed bedding ref dwg no.					
NO.	DATE	REVISION					



'H' DEPTH FROM FINISHED GRADE TO TOP OF MAIN IN METRES	TABLES FOR VALUES OF "T" (INSULATION THICKNESS) IN MILLIMETERS								'W' WIDTH OF INSULATION IN METRES
	MAINS IN LANES OR EASEMENTS		MAINS IN STREETS		DEAD END MAINS IN STREETS		DEAD END MAINS IN LANES		
	GRAVEL	CLAY	GRAVEL	CLAY	GRAVEL	CLAY	GRAVEL	CLAY	
0 - 1	*	*	*	*	*	*	*	*	*
1 - 1.25	125	100	150	125	175	150	150	125	3.7
1.25 - 1.5	100	75	125	100	150	125	125	100	3.2
1.5 - 1.8	75	50	100	75	125	100	100	75	2.6
1.8 - 2.1	50	25	75	50	100	75	75	75	2.0
2.1 - 2.4	25	0	50	25	75	50	50	25	1.4
2.4 - 2.7	0	0	25	0	50	25	25	0	1.0
2.7 - 3.0	0	0	0	0	25	0	0	0	1.0
3.0 OR MORE	0	0	0	0	0	0	0	0	-

\* INDICATES DEPTH NOT PRACTICAL

8		
7		
6		
5		
4		
3		
2		
1	06/03/20	Revised Dwg, Details & Table
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
**N.T.S.**

Checked by: 


Approved by: 

Drawn by: **L. LEEPER**

Date:  
**Feb. 22, 2011**

Drawing #:  
**4-101**

INSULATION REQUIREMENTS



**NOTES:**

1. TO BE USED WHERE CROSSING PIPE IS OPEN TO THE ATMOSPHERE (e.g. STORM SEWER, CULVERT CROSSING, etc.).
2. USE DEPTH "H" FOR INSULATION THICKNESS AND WIDTH AS PER DWG. 4-101.

8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: L. LEEPER

**INSULATION REQUIREMENTS  
CROSSING PIPE OPEN TO ATMOSPHERE**

Date: Mar. 9, 2020

Drawing #: 4-102


Scale: N.T.S.



CLASS A

LEGEND

W = TRENCH WIDTH.  
O.D. = OUTSIDE DIAMETER OF PIPE.



CLASS B

NOTES:

1. ADD 100mm TO BEDDING IN ROCK EXCAVATION.
2. TRENCH WIDTH TO BE A MINIMUM OF TWICE THE OUTSIDE DIAMETER OF THE PIPE OR TO MANUFACTURERS SPECIFICATIONS.
3. COMPACT SAND IN THE HAUNCH ZONE IN BOTH DIRECTIONS AWAY FROM THE PIPE TO THE UNDISTURBED TRENCH WALLS.
4. FOR PIPES UP TO 600mm IN DIAMETER. FOR PIPES LARGER THAN 600mm IN DIAMETER PROVIDE BEDDING DESIGN IN CONFORMANCE WITH CITY STANDARDS.

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: N / A

**PIPE ZONE BEDDING DETAILS  
(CLASS A, B)**


Date: Feb. 22, 2011

Drawing #: 4-200


Scale: N.T.S.

8		
7		
6	04/05/20	Removed "1/2 O.D." Text
5	09/03/20	Removed B-1 and Added Notes
4	23/03/18	Revised Notes
3	21/12/16	Updated Notes
2	17/04/14	Changed concrete strength
1	21/03/13	Updated concrete type
NO.	DATE	REVISION





**SECTION B-B**



**SECTION A-A**

8		
7		
6		
5		
4		
3		
2		
1	23/03/18	Revised Details
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: **L. LEEPER**

Scale: **N.T.S.**

**PIPE SUPPORT**

Date: **Feb. 22, 2011**

Drawing #: **4-300**



8		
7	23/03/18	Revised Note
6	22/11/16	Updated Dimensions
5	28/06/16	Updated Notes
4	14/04/16	Updated Dimensions
3	08/04/14	Changed grade ring thickness
2	10/12/13	Updated concrete strength
1	21/03/13	Updated concrete type
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: L. LEEPER

**900mm DIA. CATCH BASIN c/w FRAME AND COVER**

Date: Feb. 22, 2011

Drawing #: 5-100



**NOTES:**

1. UNIT COULD BE MADE UP FROM TWO ITEMS (BASE AND BARREL).
2. OPPOSITE ORIENTATION OF JOINTS IS ACCEPTABLE.
3. SEE DWG. 2-202 FOR CURB INSTALLATION DETAIL

8		
7		
6		
5		
4	23/11/18	Updated Notes
3	22/11/16	Updated Dimensions
2	28/06/16	Updated Notes
1	14/04/16	Updated Dimensions
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*



Approved by: *[Signature]*

Drawn by: L. LEEPER

**1200mm DIA C.B. MANHOLE c/w  
F-51 FRAME AND COVER WITH  
TWO PIECE SIDE INLET**

Date: Feb. 22, 2011

Drawing #: 5-101



8		
7		
6		
5		
4	04/05/20	Rem. "mm", Changed Hatch
3	09/03/20	Added Hatching to Wick Drain
2	23/03/18	Rev. C/S W/D Placement
1	14/04/16	Updated Dimensions
NO.	DATE	REVISION

**The City of Lloydminster**





Scale:  
N.T.S.

Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: N/A

**WICK DRAIN CONNECTION  
TO CATCH BASIN**

Date:  
Feb. 22, 2011  
Drawing #:  
**5-200**




**NOTES:**

1. COMPRESSIVE STRENGTH OF STRUCTURE CONCRETE AT 28 DAYS SHALL BE 32 MPa.
2. CLEAR COVER FOR REBAR ON EARTH FACE SHALL BE 75mm AND 50mm ELSEWHERE.
3. STILLING BASIN SHALL BE REQ'D FOR HIGH VELOCITY FLOWS.
4. ALL FILTER CLOTH PANEL JOINTS TO OVERLAP 100mm
5. FILTER CLOTH TYPE TO BE NON-WOVEN.
6. SEE STD. DWG. NO. 5-302 FOR BAR SCREEN.
7. RIP-RAP TO BE GABION MAT OR SACKED CONCRETE, AND EXTEND TO CHANNEL SIDES.
8. APPROPRIATE ENGINEERED REINFORCEMENT REQUIRED.
9. RIP-RAP CLASS FOR OUTLET AND CHANNEL MUST BE SELECTED BASED ON DISCHARGE VELOCITY

8		
7		
6		
5	09/03/20	Revised Drawing
4	03/01/19	Revised Drawings & Text
3	23/11/18	Revised Drawings & Text
2	08/04/14	Changed concrete strength
1	22/06/11	Drawing reference, Note 6
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: **L. LEEPER**

**POURED CONCRETE  
OUTFALL STRUCTURE**


Date: **Feb. 22, 2011**

Drawing #: **5-300**


Scale: **N.T.S.**



CROSS SECTION



ELEVATION




PLAN

PIPE DIAMETER "D" mm	GALVANIZED METAL THICKNESS mm	DIMENSIONS, mm					SLOPE "S"	BODY
		A 25 mm ±	B MAX mm	H 25 mm ±	L 38 mm ±	W 50 mm ±		
300	1.6	150	140	150	535	610	2.5	1 PC
600	1.6	250	300	150	1040	1220	2.5	1 PC
1200	2.0	350	475	225	1500	1800	2.5	1 PC
1200	2.0	460	625	305	1980	2285	2.25	2 PC


NOTES:

1. RIP-RAP TO BE PLACED AROUND OUTLET AS PER DWG. 5-304

8				<b>The City of Lloydminster</b>	Checked by:	Approved by:	Drawn by: <b>L. LEEPER</b>
7							
6							
5							
4							
3							
2							
1	11/23/18	REVISED TEXT					
NO.	DATE	REVISION	N.T.S.				



FRONT VIEW



TOP VIEW

8		
7		
6		
5		
4		
3		
2		
1	11/26/18	Removed Outlet Structure Linework
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: L. LEEPER


**BAR SCREEN FOR OUTLET  
STRUCTURE DETAIL**

Date: Feb. 22, 2011

Drawing #: 5-302



FRONT VIEW



TOP VIEW

8		
7		
6		
5		
4		
3		
2		
1	11/26/18	Removed Inlet Structure Linework
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: **L. LEEPER**



**BAR SCREEN FOR INLET  
STRUCTURE DETAIL**

Date: **Feb. 22, 2011**

Drawing #: **5-303**

Scale: **N.T.S.**





SECTION A-A

**NOTES:**

1. STILLING BASIN SHALL BE REQ'D FOR HIGH-VELOCITY FLOWS.
2. ALL FILTER CLOTH PANEL JOINTS TO OVERLAP 1.0m IN THE DIRECTION OF FLOW.
3. FILTER CLOTH TYPE TO BE NON-WOVEN
4. RIP-RAP TO BE 150-350mm IN NORMAL DIAMETER WITH 50% BEING LARGER THAN 200mm
5. RIP-RAP ABOVE PIPE TO EXTEND TO CHANNEL SIDES

8		
7		
6		
5		
4		
3		
2		
1	11/26/18	UPDATED NOTES AND TITLE
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: L. LEEPER

**ROCK RIP-RAP DETAIL FOR METAL CULVERTS OR OPEN CHANNELS**


Date: Feb. 22, 2011

Drawing #: 5-304

Scale: N.T.S.






SIGN




LOCATION

**NOTES:**




1. SIGNS WILL BE PLACED AT THE HIGH WATER LEVEL AT ALL INLET AND OUTLET LOCATIONS.
2. ALL SIGNS TO BE SECURELY FASTENED WITH NYLON LOCKING NUTS.
3. SIGN AND LETTING TO BE SCREENED REFLECTIVE SHEETING ON SIGN GRADE ALUMINIUM.
4. SUBMIT ONE COMPLETE SIGN FOR APPROVAL BY ENGINEER PRIOR TO INSTALLATION.
5. POST TO BE 3100mm GALVANIZED STEEL U-CHANNEL SIGN POST, EMBEDDED IN CONCRETE AS PER DWG. 5-406


8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>
5	04/05/20	Revised Text Height		<b>INLET INDICATOR POST DETAIL</b>		
4	09/03/20	Revised Details				
3	03/12/19	Revised Notes				
2	26/11/18	Revised Notes				
1	2/3/17	Revised Lineweight				
NO.	DATE	REVISION	Scale: <b>N.T.S.</b>			Date: <b>Dec 23, 2016</b>
						Drawing #: <b>5-400</b>



**NOTES:**




1. SIGNS WILL BE PLACED AT ACCESS ENTRANCE TO THE STORM WATER MANAGEMENT FEATURE AS APPROVED BY WASTE SERVICES.
2. ALL SIGNS TO BE SECURELY FASTENED WITH NYLON LOCKING NUTS.
3. SIGN AND LETTERING TO BE SCREENED REFLECTIVE SHEETING ON SIGN GRADE ALUMINIUM.
4. SUBMIT ONE COMPLETE SIGN FOR APPROVAL BY CITY PRIOR TO INSTALLATION.
5. POST TO BE 3100mm GALVANIZED STEEL U-CHANNEL SIGN POST, EMBEDDED IN CONCRETE AS PER DWG. 5-406


			<b>The City of Lloydminster</b>			
8				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>
7				<b>STORMWATER STORAGE WETLAND SIGN</b>		Date: <b>Dec 23, 2016</b>
6			Scale: <b>N.T.S.</b>			Drawing #: <b>5-401</b>
5						
4	10/03/20	Changed Water to Waste				
3	11/26/19	Revised Signage, Colour, Notes				
2	11/26/18	Revised Notes				
1	2/3/17	Revised Lineweight				
NO.	DATE	REVISION				



**NOTES:**




1. SIGNS WILL BE PLACED AT ACCESS ENTRANCE TO THE STORM WATER MANAGEMENT FEATURE AS APPROVED BY WASTE SERVICES.
2. ALL SIGNS TO BE SECURELY FASTENED WITH NYLON LOCKING NUTS.
3. SIGN AND LETTERING TO BE SCREENED REFLECTIVE SHEETING ON SIGN GRADE ALUMINIUM.
4. SUBMIT ONE COMPLETE SIGN FOR APPROVAL BY ENGINEER PRIOR TO INSTALLATION.
5. POST TO BE 3100mm GALVANIZED STEEL U-CHANNEL SIGN POST, EMBEDDED IN CONCRETE AS PER DWG. 5-406.


8			<b>The City of Lloydminster</b>				
7				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>	
6				<b>STORMWATER STORAGE POND SIGN</b>			
5							Date: <b>Dec 23, 2016</b>
4	10/03/20	Changed Water to Waste					Revision #: <b>5-402</b>
3	11/26/19	Revised Signage, Colour, Notes					
2	11/26/18	Revised Notes	Scale: <b>N.T.S.</b>				
1	2/3/17	Revised Lineweight					
NO.	DATE	REVISION					



**NOTES:**





1. SIGNS WILL BE PLACED AT ACCESS ENTRANCE TO THE STORM WATER MANAGEMENT FEATURE AS APPROVED BY WASTE SERVICES.
2. ALL SIGNS TO BE SECURELY FASTENED WITH NYLON LOCKING NUTS.
3. SIGN AND LETTERING TO BE SCREENED REFLECTIVE SHEETING ON SIGN GRADE ALUMINIUM.
4. SUBMIT ONE COMPLETE SIGN FOR APPROVAL BY CITY PRIOR TO INSTALLATION.
5. POST TO BE 3100mm GALVANIZED STEEL U-CHANNEL SIGN POST, EMBEDDED IN CONCRETE AS PER DWG. 5-406




8			<b>The City of Lloydminster</b>				
7				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>	
6				<b>STORMWATER STORAGE SITE SIGN</b>			
5							Date: <b>Dec 23, 2016</b>
4	10/03/20	Changed Water to Waste					Drawing #: <b>5-403</b>
3	11/26/19	Revised Signage, Colour, Notes					
2	11/26/18	Revised Notes	Scale: <b>N.T.S.</b>				
1	2/3/17	Revised Lineweight					
NO.	DATE	REVISION					



**NOTES:**

1. SIGNS WILL BE PLACED AT ACCESS ENTRANCE TO THE STORM WATER MANAGEMENT FEATURE AS APPROVED BY WASTE SERVICES.
2. ALL SIGNS TO BE SECURELY FASTENED WITH NYLON LOCKING NUTS.
3. SIGN AND LETTERING TO BE SCREENED REFLECTIVE SHEETING ON SIGN GRADE ALUMINIUM.
4. SUBMIT ONE COMPLETE SIGN FOR APPROVAL BY CITY PRIOR TO INSTALLATION.
5. POST TO BE 3100mm GALVANIZED STEEL U-CHANNEL SIGN POST, EMBEDDED IN CONCRETE AS PER DWG. 5-406


8			<b>The City of Lloydminster</b>						
7				Checked by: 	Approved by: 	Drawn by: A. EDWARDS			
6									
5				<b>STORMWATER CHANNEL SIGN</b>		Date: Dec 23, 2016			
4	10/03/20	Changed Water to Waste				Scale: N.T.S.			Revision #: 5-404
3	11/26/19	Replaces 5-404 (now 5-405)							
2	11/26/18	Revised Notes							
1	2/3/17	Revised Lineweight							
NO.	DATE	REVISION							



**NOTES:**

1. TO ACCOMPANY DWGS. 5-401, 5-402, 5-403.
2. ON SIGNS 5-403 & 5-404, SYMBOLS TO BE 200mm x 200mm.

8			<b>The City of Lloydminster</b>				
7							
6			 Scale: N.T.S.	Checked by: 	Approved by: 	Drawn by: A. EDWARDS	
5	04/05/20	Changed Text Height		<b>STORMWATER STORAGE SITE SIGN DETAILS</b>			
4	10/03/20	Changed Text Height					
3	27/11/19	Changed DWG No. from 5-404					Date: Jan 11, 2017
2	2/3/17	Revised Notes and Arrows					Drawing #: 5-405
1	2/3/17	Revised Lineweight					
NO.	DATE	REVISION					



**NOTES:**

1. U-CHANNEL TO BE EMBEDDED WITHIN CONCRETE BASE, EXTENDING 200 mm ABOVE FINISHED GROUND
2. MOUNT SIGN ON U-CHANNEL POST. SECURE POST TO U-CHANNEL IN CONCRETE BASE

8		
7		
6		
5		
4		
3	04/05/20	Revised "MM" to "mm"
2	10/03/20	Added Text
1	27/11/19	Changed DWG No. from 5-405
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: J.IDIOH


Scale: N.T.S.

**TYPICAL NOTICE SIGN**


Date: Jan 17, 2019

Drawing #: 5-406





PLAN VIEW



SECTION VIEW

8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: J.IDIOH

**TYPICAL STORMWATER STORAGE POND**

Date: Jan. 10, 2019

Drawing #: 5-500



8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: J.IDIOH

**TYPICAL STORMWATER STORAGE POND FOREBAY**

Date: Jan. 09, 2019

Drawing #: 5-501

Scale: N.T.S.



**NOTES:**

1. VALVE BOX TOPS TO BE SET FLUSH WITH SURFACE IN BOULEVARDS, GREEN SPACES AND CONCRETE SIDEWALKS.
2. ALL BOLTS TO BE WRAPPED IN DENSO OR PETROGUARD PETROLATUM TAPE.
3. CAD WELD TO BE COVERED BY DENSO OR PETROGUARD PETROLATUM TAPE.

8		
7		
6		
5	10/03/20	Revised Drawing
4	3/22/18	Revised Notes
3	22/11/16	Revised Notes
2	6/14/16	Revised Notes
1	4/14/16	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: **L. LEEPER**

**WATER VALVE INSTALLATION**

Date: **Feb. 22, 2011**




Drawing #: **6-100**


Scale: **N.T.S.**



**NOTES:**

1. VALVE BOX COVER TO BE SET FLUSH WITH SURFACE IN BOULEVARDS, GREEN SPACES AND CONCRETE SIDEWALKS.
2. ALL BOLTS TO BE WRAPPED IN DENSO OR PETROGUARD PETROLATUM TAPE.
3. SACRIFICIAL ANODE TO BE INSTALLED AS PER STANDARD DRAWING 6-401.

8			<b>The City of Lloydminster</b>			
7						
6	22/06/20	Rev. Dim to Nut	 Scale: N.T.S.	Checked by: 	Approved by: 	Drawn by: N/A
5	05/05/20	Rev. Nut, Removed "mm"				
4	27/11/18	Revised Notes & Drawing				
3	22/11/16	Revised Notes				
2	6/14/16	Revised Notes				
1	4/14/16	Revised Notes				
NO.	DATE	REVISION	<b>HOT TAPPING CONNECTION</b>			Date: Feb. 22, 2011
						Drawing #: <b>6-101</b>



**NOTES:**

1. HYDRANT TO BE SET PLUMB WITH BARREL EXTENSIONS TO SUIT DEPTH OF HYDRANT LEAD. HYDRANT LEAD TO BE SET LEVEL WITH A MIN. OF 3.0m OF COVER ABOVE TOP OF PIPE. EXTENSION TO BE INSTALLED BETWEEN HYDRANT AND TOP OF BARREL AS REQUIRED.
2. ALL THRUST BLOCKING TO BE AGAINST UNDISTURBED TRENCH WALL WITH DRAIN HOLES CLEAR OF CONCRETE.
3. VALVE BOX TO BE INSTALLED IN VERTICAL POSITION WITH TOP FLUSH WITH FINISHED GRADE.
4. HYDRANT SHALL BE COMPRESSION TYPE AS SPECIFIED.
5. ALL CAST IRON VALVES AND FITTINGS SHALL BE CATHODICALLY PROTECTED BY SACRIFICIAL ANODES AS PER DWG. 6-401. CAD WELDS TO BE COVERED WITH DENSO OR PETROGUARD PETROLATUM TAPE.
6. HYDRANT TO BE SUPPLIED WITH BREAKAWAY FLANGE INSTALLED ABOVE GROUND DIRECTLY BELOW THE BODY FLANGE..
7. CONCRETE TO BE 25MPa TYPE HS.
8. **ALL HYDRANTS TO HAVE THREADS CONFORMING TO SASKATCHEWAN SPECIFICATIONS:**
  - HOSE CONNECTION: 6 THREADS PER INCH, OUTSIDE DIAMETER 82.55mm
  - PUMPER CONNECTION: 6 THREADS PER INCH, MAJOR DIAMETER 123.11mm, PITCH DIAMETER 119.76mm, MINOR DIAMETER 116.41mm.
9. ALL BOLTS BELOW GROUND TO BE WRAPPED WITH DENSO OR PETROGUARD PETROLATUM TAPE.
10. INSIDE ROD COUPLING (TRAFFIC TYPE) TO BE LOCATED WITHIN 50mm OF BREAKAWAY FLANGE.

8		
7	05/05/20	Removed "mm" From Dims
6	3/22/18	Revised Notes
5	22/11/16	Revised Notes
4	05/07/16	Revised Notes
3	4/14/16	Revised Notes
2	28/05/14	Removed drain plug ref.
1	21/03/13	Updated concrete type
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: 


Approved by: 

Drawn by: L. LEEPER

Date:  
Feb. 22, 2011

Drawing #:  
**6-102**

HYDRANT INSTALLATION



**NOTES:**

1. SERVICE BOX AND VALVE CASING TO BE INSTALLED PLUMB.
2. DIAMETER OF SERVICE PIPE TO BE UNIFORM FROM CORPORATION STOP.
3. MINIMUM COVER OVER SERVICE PIPE TO BE 2.8m.
4. CAPS TO BE INSTALLED FLUSH WITH FINISHED GROUND.
5. NPT FITTING TO BE COMPRESSION-TYPE, FEMALE THREADS.

8		
7	05/05/20	Revised Notes Text Height
6	10/03/20	Revised Text Styles
5	01/05/19	Revised Notes
4	27/11/18	Revised Drawings
3	28/06/16	Revised Notes
2	14/04/16	Revised Notes
1	08/04/14	Changed drawing title
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: N / A

**PERMANENT BLOW OFF VALVE  
DETAIL**




Date: Feb. 22, 2011






Drawing #: 6-200



**NOTES:**

1. VALVES TO BE ADJUSTED TO FINISHED GRADE PRIOR TO PLACING ASPHALTIC CONCRETE SURFACE COURSE.
2. TOP OF VALVES IN SIDEWALKS SHALL BE SET FLUSH WITH THE CONCRETE SURFACE.
3. TOP OF VALVES IN BOULEVARDS SHALL BE SET FLUSH WITH THE BOULEVARD FINISHED SURFACE ELEVATION.

8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: <b>L. LEEPER</b>
5				<b>VALVE ADJUSTMENT DETAIL</b>	Date: <b>Feb. 22, 2011</b>	
4			Drawing #: <b>6-201</b>			
3	10/03/20	Revised Dimension	Scale: <b>N.T.S.</b>			
2	3/22/18	Revised Notes				
1	4/14/16	Added Nut and Stone Guard				
NO.	DATE	REVISION				




PIPE SIZE	FITTINGS															
	TEE & DEAD END				11 1/4° & 22 1/2° BENDS				45° BEND				90° BEND			
	A	B	C	BEARING AREA	A	B	C	BEARING AREA	A	B	C	BEARING AREA	A	B	C	BEARING AREA
(mm)	(mm)	(mm)	(m <sup>2</sup> )	(mm)	(mm)	(mm)	(m <sup>2</sup> )	(mm)	(mm)	(mm)	(m <sup>2</sup> )	(mm)	(mm)	(mm)	(m <sup>2</sup> )	
150	348	100	275	0.244	159	75	225	0.095	311	75	225	0.187	575	75	225	0.345
200	433	150	400	0.433	211	100	300	0.169	415	100	300	0.332	766	100	300	0.613
250	521	200	525	0.677	264	125	375	0.264	518	125	375	0.518	958	125	375	0.958
300	609	250	650	0.975	317	150	450	0.380	622	150	450	0.746	1149	150	450	1.379
400	867	300	800	1.733	423	200	600	0.676	829	200	600	1.327	1532	200	600	2.451
450	954	350	925	2.194	476	225	675	0.856	933	225	675	1.679	1724	225	675	3.102
600	1393	400	1100	3.900	634	300	900	1.522	1244	300	900	2.985	2298	300	900	5.515
750	1741	500	1375	6.094	793	375	1125	2.378	1555	375	1125	4.664	2873	375	1125	8.618

**NOTES:**


1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED.
2. DESIGN BASIS:
  - a. HYDRAULIC DESIGN PRESSURE 690 kPa (100 psi).
  - b. SOIL BEARING CAPACITY 50 kPa (1044 lb/sq.ft) (SOFT CLAY)
3. CONCRETE THRUST BLOCK BEARING SURFACE AREA AND PARAMETER 'A', 'B', & 'C' MUST BE ADJUSTED IF HYDRAULIC DESIGN PRESSURE AND SOIL BEARING CAPACITY ARE DIFFERENT THAN SHOWN IN ITEM 2, DESIGN BASIS.
4. HYDRAULIC DESIGN PRESSURE MUST INCLUDE HIGHEST OPERATING PRESSURE SCENARIO WITH SURGE PRESSURE INCLUDED.
5. TEMPORARY BLOCKING MUST BE APPROVED BY THE ENGINEER.
6. CONCRETE STRENGTH SHALL BE 25 MPa AT 28 DAYS, TYPE HS
7. CONCRETE TO BE CLEAR OF BELLS AND TO BEAR AGAINST UNDISTURBED TRENCH WALLS.
8. CONCRETE TO BE PLACED UNDER ALL FITTINGS.
9. CONCRETE TO BE CURED FOR 24 HOURS PRIOR TO BACKFILLING.
10. BOND BREAKER TO BE USED BETWEEN CONCRETE AND FITTINGS.
11. IF THE DESIGN IS BASED ON INFORMATION NOT VERIFIED IN THE FIELD AND NOT SUPPORTED BY HYDRAULIC MODELING / CALCULATIONS, A MIN. FACTOR OF SAFETY OF 1.50 SHOULD BE APPLIED TO ALL TABULATED BEARING AREAS.

8			<b>The City of Lloydminster</b>
7			
6			
5			
4	10/03/20	Reviewed Notes	 Checked by: Approved by: Drawn by: <b>L. LEEPER</b>
3	27/11/18	Reviewed Notes	
2	17/04/14	Changed concrete strength	<b>POURED CONCRETE THRUST BLOCKS FOR HORIZONTAL TEES AND BENDS</b>
1	24/03/14	Changed concrete strength	
NO.	DATE	REVISION	Scale: <b>N.T.S.</b> Date: <b>Feb. 22, 2011</b> Drawing #: <b>6-300</b>





ELEVATION







SECTION A-A

PIPE SIZE	FITTINGS							
	11 1/4° & 22 1/2° BENDS				45° BEND			
	A	B	C	BEARING AREA	A	B	C	BEARING AREA
	(mm)	(mm)	(mm)	(m <sup>2</sup> )	(mm)	(mm)	(mm)	(m <sup>2</sup> )
150	106	450	375	0.095	207	450	375	0.187
200	169	500	400	0.169	332	500	400	0.332
250	240	550	425	0.264	471	550	425	0.518
300	317	600	450	0.380	662	600	450	0.746
400	483	700	500	0.676	948	700	500	1.327
450	571	750	525	0.856	1119	750	525	1.679
600	845	900	600	1.522	1658	900	600	2.985
750	1132	1050	675	2.378	2221	1050	675	4.664


NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED.
2. DESIGN BASIS:
  - a. HYDRAULIC DESIGN PRESSURE 690 kPa (100 psi).
  - b. SOIL BEARING CAPACITY 50 kPa (1044 lb/sq.ft) (SOFT CLAY)
3. CONCRETE THRUST BLOCK BEARING SURFACE AREA AND PARAMETER 'A', 'B', & 'C' MUST BE ADJUSTED IF HYDRAULIC DESIGN PRESSURE AND SOIL BEARING CAPACITY ARE DIFFERENT THAN SHOWN IN ITEM 2, DESIGN BASIS.
4. HYDRAULIC DESIGN PRESSURE MUST INCLUDE HIGHEST OPERATING PRESSURE SCENARIO WITH SURGE PRESSURE INCLUDED.
5. TEMPORARY BLOCKING MUST BE APPROVED BY THE ENGINEER.
6. CONCRETE STRENGTH SHALL BE 25 MPa AT 28 DAYS, TYPE HS.
7. CONCRETE TO BE CLEAR OF BELLS AND TO BEAR AGAINST UNDISTURBED TRENCH WALLS.
8. CONCRETE TO BE PLACED UNDER ALL FITTINGS.
9. CONCRETE TO BE CURED FOR 24 HOURS PRIOR TO BACKFILLING.
10. BOND BREAKER TO BE USED BETWEEN CONCRETE AND FITTINGS.
11. IF THE DESIGN IS BASED ON INFORMATION NOT VERIFIED IN THE FIELD AND NOT SUPPORTED BY HYDRAULIC MODELING / CALCULATIONS, A MIN. FACTOR OF SAFETY OF 1.50 SHOULD BE APPLIED TO ALL TABULATED BEARING AREAS.

8				<b>The City of Lloydminster</b>		
7				Checked by: 	Approved by: 	Drawn by: L. LEEPER
6				<b>POURED CONCRETE THRUST BLOCKS FOR VERTICAL BENDS (DOWNWARD THRUST)</b>		
5				Date: Jan. 22, 2011		
4	10/03/20	Revised Notes		Drawing #: 6-301		
3	23/03/18	Changed line weights				
2	17/04/14	Changed concrete strength				
1	24/03/14	Changed concrete strength				
NO.	DATE	REVISION	Scale: N.T.S.			



ELEVATION








SECTION A-A

PIPE SIZE	FITTINGS					
	11 1/4° & 22 1/2° BENDS			45° BEND		
	BLOCK VOL.	C	BEARING AREA	BLOCK VOL.	C	BEARING AREA
	(m <sup>3</sup> )	(mm)	(m <sup>2</sup> )	(m <sup>3</sup> )	(mm)	(m <sup>2</sup> )
150	0.4	375	0.019	0.7	375	0.071
200	0.7	400	0.033	1.3	400	0.127
250	1.1	425	0.052	2.0	425	0.198
300	1.6	450	0.074	2.9	450	0.286
400	2.8	500	0.132	5.2	500	0.508
450	3.6	525	0.167	6.6	525	0.643
600	6.3	600	0.297	11.7	600	1.142
750	9.9	675	0.464	18.3	675	1.785

**NOTES:**

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED.
2. DESIGN BASIS:
  - a. HYDRAULIC DESIGN PRESSURE 690 kPa (100 psi).
  - b. SOIL BEARING CAPACITY 50 kPa (1044 lb/sq.ft) (SOFT CLAY)
3. CONCRETE THRUST BLOCK BEARING SURFACE AREA AND PARAMETER 'A', 'B', & 'C' MUST BE ADJUSTED IF HYDRAULIC DESIGN PRESSURE AND SOIL BEARING CAPACITY ARE DIFFERENT THAN SHOWN IN ITEM 2, DESIGN BASIS.
4. HYDRAULIC DESIGN PRESSURE MUST INCLUDE HIGHEST OPERATING PRESSURE SCENARIO WITH SURGE PRESSURE INCLUDED.
5. TEMPORARY BLOCKING MUST BE APPROVED BY THE ENGINEER.
6. CONCRETE STRENGTH SHALL BE 25 MPa AT 28 DAYS, TYPE HS.
7. CONCRETE TO BE CLEAR OF BELLS AND TO BEAR AGAINST UNDISTURBED TRENCH WALLS.
8. CONCRETE TO BE PLACED UNDER ALL FITTINGS.
9. CONCRETE TO BE CURED FOR 24 HOURS PRIOR TO BACKFILLING.
10. BOND BREAKER TO BE USED BETWEEN CONCRETE AND FITTINGS.
11. IF THE DESIGN IS BASED ON INFORMATION NOT VERIFIED IN THE FIELD AND NOT SUPPORTED BY HYDRAULIC MODELING / CALCULATIONS, A MIN. FACTOR OF SAFETY OF 1.50 SHOULD BE APPLIED TO ALL TABULATED BEARING AREAS.




8		<b>The City of Lloydminster</b>		
7			Checked by: 	
6			Approved by: 	
5			Drawn by: <b>L. LEEPER</b>	
4	10/03/20		Revised Notes	<b>POURED CONCRETE THRUST BLOCKS FOR VERTICAL BENDS (UPWARD THRUST)</b>
3	23/03/18		Changed line weights	
2	17/04/14	Changed concrete strength		
1	24/03/14	Changed concrete strength	Date: <b>Jan. 22, 2011</b>	
NO.	DATE	REVISION	Drawing #: <b>6-302</b>	
			Scale: <b>N.T.S.</b>	




MINIMUM DIMENSIONS IN mm's				
SIZE OF PIPE	A	B	C	BEARING AREA
100	430	250	200	0.11
150	700	350	200	0.24
200	870	500	200	0.43
250	1040	650	275	0.68
300	1220	800	350	0.98
400	1730	1000	400	1.73
450	1910	1150	475	2.19
600	2790	1400	500	3.90
750	3480	1750	625	6.09

**NOTES:**

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED.
2. DESIGN BASIS:
  - a. HYDRAULIC DESIGN PRESSURE 690 kPa (100 psi).
  - b. SOIL BEARING CAPACITY 50 kPa (1044 lb/sq.ft) (SOFT CLAY)
3. CONCRETE THRUST BLOCK BEARING SURFACE AREA AND PARAMETER 'A', 'B', & 'C' MUST BE ADJUSTED IF HYDRAULIC DESIGN PRESSURE AND SOIL BEARING CAPACITY ARE DIFFERENT THAN SHOWN IN ITEM 2, DESIGN BASIS.
4. HYDRAULIC DESIGN PRESSURE MUST INCLUDE HIGHEST OPERATING PRESSURE SCENARIO WITH SURGE PRESSURE INCLUDED.
5. TEMPORARY BLOCKING MUST BE APPROVED BY THE ENGINEER.
6. CONCRETE STRENGTH SHALL BE 25 MPa AT 28 DAYS, TYPE HS.
7. CONCRETE TO BE CLEAR OF BELLS AND TO BEAR AGAINST UNDISTURBED TRENCH WALLS.
8. CONCRETE TO BE PLACED UNDER ALL FITTINGS.
9. CONCRETE TO BE CURED FOR 24 HOURS PRIOR TO BACKFILLING.
10. BOND BREAKER TO BE USED BETWEEN CONCRETE AND FITTINGS.
11. IF THE DESIGN IS BASED ON INFORMATION NOT VERIFIED IN THE FIELD AND NOT SUPPORTED BY HYDRAULIC MODELING / CALCULATIONS, A MIN. FACTOR OF SAFETY OF 1.50 SHOULD BE APPLIED TO ALL TABULATED BEARING AREAS.

8		<b>The City of Lloydminster</b>		
7			Checked by: 	Approved by: 
6			Drawn by: <b>L. LEEPER</b>	
5			Date: <b>Feb. 22, 2011</b>	
4	10/03/20		Drawing #: <b>6-303</b>	
3	23/03/18	<b>POURED CONCRETE THRUST BLOCKS FOR DEAD-ENDS</b>		
2	17/04/14	<b>REVISION</b>		
1	24/03/14	Scale: <b>N.T.S.</b>		
NO.	DATE			



MINIMUM DIMENSIONS IN mm				
SIZE OF PIPE	A	B	C	BEARING AREA
100	430	250	200	0.11
150	700	350	200	0.24
200	870	500	200	0.43
250	1040	650	275	0.68
300	1220	800	350	0.98
400	1730	1000	400	1.73
450	1910	1150	475	2.19
600	2790	1400	500	3.90
750	3480	1750	625	6.09

**NOTES:**

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED.
2. SAW CUT PIPE TO BE ABANDONED.
3. REMOVE PIPE FROM TEE ON MAIN. INSTALL PLUG ON TEE.
4. PLACE BACKFILL (COMPACTED TO 100% S.P.D.) TO A DEPTH OF TWO TIMES DIMENSION "B".
5. CUT 10mm THICK STEEL PLATE TO RECTANGULAR DIMENSIONS "A" x "B", WELD STEEL PIPE TO CENTRE OF PLATE.
6. DRIVE PIPE INTO BACKFILLED MATERIAL, CREATING A SPACE A MINIMUM OF DIMENSION "C" IN LENGTH BETWEEN THE PLUG AND THE FACE OF THE STEEL PLATE.
7. POUR CONCRETE THRUST BLOCK, COVERING THE ENTIRE TEE.
8. CONCRETE STRENGTH MUST BE 25 MPa AT 28 DAYS, TYPE HS.
9. CONCRETE TO BE CLEAR OF BELLS AND TO BEAR AGAINST EXCAVATED TRENCH WALLS AND PLATE.
10. CONCRETE TO BE PLACED UNDER ALL FITTINGS.
11. CONCRETE TO BE CURED FOR 24 HOURS PRIOR TO BACKFILLING.

8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**




Scale: N.T.S.

Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: L. LEEPER

**POURED CONCRETE THRUST BLOCKS FOR DEAD-ENDS IN DISTURBED SOIL**

Date: Oct. 29, 2018

Drawing #: 6-304



**NOTES:**

1. MINIMUM DISTANCE FROM ANODE TO PIPE, FITTING, VALVE, OR HYDRANT IS 150mm.
2. INSTALL ANODE AT APPROXIMATE PIPE DEPTH IN NATIVE SOIL.
3. ZINC ANODES TO BE EMBEDDED INTO TRENCH WALL TO PROVIDE FOR A MINIMUM OF 50mm OF NATIVE CLAY COMPLETELY SURROUNDING THE ANODE.
4. ANODES TO BE AT LEAST 300mm CLEAR OF THRUST BLOCK
5. CAD WELDS TO BE COVERED IN DENSO OR PETROGUARD PETROLATUM TAPE.
6. 3 LITRES OF WATER TO BE POURED ON ANODE FOLLOWING PLACEMENT TO ACTIVATE.
7. ANODE LEADS TO BE 2m IN LENGTH.

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: **L. LEEPER**


**ANODE INSTALLATION AT HYDRANT**

Date: **Feb. 22, 2011**

Drawing #: **6-400**

Scale: **N.T.S.**

8		
7		
6		
5		
4		
3	3/22/18	Revised Notes
2	22/11/16	Revised Notes
1	4/14/16	Revised Notes
NO.	DATE	REVISION




**NOTES:**

1. MINIMUM DISTANCE FROM ANODE TO PIPE, FITTING, VALVE, OR HYDRANT IS 150mm.
2. INSTALL ANODE AT APPROXIMATE PIPE DEPTH IN NATIVE SOIL.
3. BOND WIRES MAY BE USED TO PROTECT UP TO TWO FITTINGS WITH ONE ANODE WHEN DIMENSION 'A' DOES NOT EXCEED ONE (1) METER.
4. ALL ZINC ANODES ON FITTINGS AND VALVES ARE 2.3kg.
5. ZINC ANODES TO BE EMBEDDED INTO TRENCH WALL TO PROVIDE FOR A MINIMUM OF 50mm OF NATIVE CLAY COMPLETELY SURROUNDING THE ANODE.
6. CAD WELDS TO BE COVERED IN DENSO OR PETROGUARD PETROLATUM TAPE.
7. 3 LITRES OF WATER TO BE POURED ON ANODE FOLLOWING PLACEMENT TO ACTIVATE.
8. ANODE LEADS TO BE 2m IN LENGTH.

8		
7		
6		
5		
4		
3	3/22/18	Revised Notes
2	22/11/16	Revised Notes
1	4/14/16	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*






Approved by: *[Signature]*

**TYPICAL ANODE INSTALLATION  
FOR METALLIC FITTINGS USED  
WITH PVC WATER MAINS**

Drawn by:  
**L. LEEPER**

Date:  
Feb. 22, 2011

Drawing #:  
**6-401**



8	22/06/20	Added "m" to Dim
7	05/05/20	Added "m" to Dims, Chg Txt Ht.
6	10/03/20	Added Dimension
5	04/14/16	Removed Gas Line & Drawing dimensions
4	04/14/16	Added Hydrant Dimension
3	06/03/13	Revised Side Lot Dimension
2	22/10/12	Revised Side Lot Dimension
1	14/02/12	Revised Dimensioning
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: N/A

**TYPICAL LATERAL SERVICE LOCATION DETAIL**

Date: Feb. 22, 2011

Drawing #: 7-100

Scale: N.T.S.



**NOTES:**

1. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.
2. THE END OF THE WATER SERVICE SHALL NOT BE CRIMPED CLOSED, PERMEABLE FILTER CLOTH WILL BE USED TO PREVENT INTRUSION OF DEBRIS AND TO ALLOW TESTING FLOW OF CURBSTOP.
3. STORM SERVICE SHALL ALWAYS BE LOCATED CLOSEST TO PROPERTY LINE.
4. INSERTABLE TEES MAY BE USED ON CONCRETE MAINS AND OPEN PROFILE PVC MAINS.

8		
7	22/06/20	Revised Note 1
6	10/03/20	Added Union Block to Water
5	3/22/18	Revised Notes
4	22/11/16	Revised Notes
3	04/14/16	Updated Dimensions & Notes
2	09/04/14	Added property line for clarity
1	14/02/12	Revised drawing name & notes.
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: L. LEEPER


**RESIDENTIAL LATERAL SERVICE DETAIL**

Date: Feb. 22, 2011

Drawing #: 7-101




Scale: N.T.S.






**NOTES:**




1. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.
2. STORM SERVICE SHALL ALWAYS BE LOCATED CLOSEST TO PROPERTY LINE.
3. SIZE OF THE SERVICES BEYOND THE PROPERTY LINE MAY BE REDUCED BY THE DEVELOPER AS REQUIRED.
4. INSERTABLE TEES MAY BE USED ON CONCRETE MAINS AND OPEN PROFILE PVC MAINS


8				<b>The City of Lloydminster</b>		Checked by: 	Approved by: 	Drawn by:	N / A							
7				<b>MULTI-FAMILY SERVICE DETAIL WITH STORM SERVICE</b>						Date:	Apr. 30, 2014					
6										Scale:	<b>7-102</b>					
5	22/06/20	Revised Note 1								N.T.S.						
4	28/11/18	Revised Notes														
3	22/11/16	Revised Notes														
2	4/14/16	Revised Notes														
1	24/02/15	Rem. Saddle from WM, Chg. Title														
NO.	DATE	REVISION														



**NOTES:**

1. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.
2. SIZE OF THE SERVICES BEYOND THE PROPERTY LINE MAY BE REDUCED BY THE DEVELOPER AS REQUIRED.
3. INSERTABLE TEES MAY BE USED ON CONCRETE MAINS AND OPEN PROFILE PVC MAINS.


8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: N/A
5	22/06/20	Revised Note 1		<b>MULTI-FAMILY SERVICE DETAIL</b>	Date: Apr. 30, 2014	
4	3/22/18	Revised Notes			Drawing #: 7-103	
3	22/11/16	Revised Notes				
2	4/14/16	Revised Notes				
1	24/02/15	Changed dwg title & detail text				
NO.	DATE	REVISION	Scale: N.T.S.			



**NOTES:**


1. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.
2. STORM SERVICE SHALL ALWAYS BE LOCATED CLOSEST TO PROPERTY LINE.
3. SIZE OF THE SERVICES BEYOND THE PROPERTY LINE MAY BE REDUCED BY THE DEVELOPER AS REQUIRED.
4. INSERTABLE TEES MAY BE USED ON CONCRETE MAINS AND OPEN PROFILE PVC MAINS


8			<b>The City of Lloydminster</b>	
7				
6			Checked by: 	Approved by: 
5				Drawn by: N/A
4	22/06/20	Revised Note 1		<b>COMMERCIAL SERVICE DETAIL WITH STORM SERVICE</b>
3	28/11/18	Revised Notes		
2	22/11/16	Revised Notes		
1	24/02/15	Rem. Saddle from WM, Chg. dwg no.		
NO.	DATE	REVISION		
			Scale: N.T.S.	Date: Apr. 30, 2014
				Drawing #: 7-104



**NOTES:**


1. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.
2. SIZE OF THE SERVICES BEYOND THE PROPERTY LINE MAY BE REDUCED BY THE DEVELOPER AS REQUIRED.
3. INSERTABLE TEES MAY BE USED ON CONCRETE MAINS AND OPEN PROFILE PVC MAINS.

8			<b>The City of Lloydminster</b>				
7							
6				Checked by: <i>[Signature]</i>	Approved by: <i>[Signature]</i>	Drawn by: N/A	
5				<b>COMMERCIAL SERVICE DETAIL</b>			
4	22/06/20	Revised Note 1					Date: Feb.24, 2015
3	28/11/18	Revised Notes					Drawing #: 7-105
2	22/11/16	Revised Notes					
1	24/02/15	Changed dwg no., added MH	Scale: N.T.S.				
NO.	DATE	REVISION					




**NOTES:**


1. IN THE CASE OF MORE THAN 6 CONNECTIONS INTO A MANHOLE, A DETAIL DRAWING SHALL BE SUBMITTED TO THE CITY OF LLOYDMINSTER FOR APPROVAL.
2. MAXIMUM HEIGHT - INVERT OF INCOMING SERVICE PIPES SHALL NOT EXCEED 300mm ABOVE THE INVERT OF THE OUTLET MAIN LINE PIPE.
3. MINIMUM HEIGHT - MATCH CROWN OF SERVICE PIPES WITH CROWN OF OUTLET MAIN LINE PIPE.
4. PIPE BENCHING TO ACCOMMODATE BRANCH CONNECTIONS.
5. SERVICE CONNECTIONS INTO BARREL TO BE MACHINE CORED OR CUT, AND SEALED WITH NON-SHRINK GROUT AS PER DWG. 3-207
6. MIN. 100 FOR 1 SERVICE, MIN. 200 FOR 2 SERVICES.



ALTERNATE #1



TYPICAL



ALTERNATE #2

8		
7		
6		
5		
4		
3		
2	22/06/20	Revised Note 1
1	11/28/18	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**




Scale: N.T.S.

Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: A. EDWARDS

**SERVICE CONNECTION  
DETAILS FOR SEWER  
MANHOLE IN CUL DE SAC**


Date: April 14, 2016

Drawing #: 7-106



**NOTES:**

1. ALL TRENCH WALLS SHALL BE SLOPED OR SHORED IN CONFORMANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY REGULATIONS CURRENTLY IN EFFECT
2. OD = OUTSIDE DIAMETER
3. SERVICE CONNECTIONS TO BE MADE AT THE 10:00 OR 2:00 POSITION.
4. INSTALL 100mm SERVICE PIPE FROM PLUG TO THE HOUSE CONNECTION.  
 MIN SLOPE = 2.0%  
 MAX BEND = 45° TOTAL  
 MAX NUMBER OF BENDS = 2
5. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.



**SECTION A-A**

8		
7		
6		
5	22/06/20	Revised Note 5
4	10/03/20	Revised Notes & Dwg
3	3/22/18	Revised Notes
2	4/14/16	Revised Notes
1	08/04/14	Added property line to Sec. A-A
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: N/A

**RESIDENTIAL NON - RISER  
TYPE SANITARY SERVICE  
CONNECTION**


Date: Feb. 22, 2011

Drawing #: 7-200



**NOTES:**

1. ALL TRENCH WALLS SHALL BE SLOPED OR SHORED IN CONFORMANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY REGULATIONS CURRENTLY IN EFFECT
2. OD = OUTSIDE DIAMETER
3. SERVICE CONNECTIONS TO BE MADE AT THE 10:00 OR 2:00 POSITION.
4. INSTALL 100mm SERVICE PIPE FROM PLUG TO THE HOUSE CONNECTION.  
 MIN SLOPE = 2.0%  
 MAX BEND = 45° TOTAL  
 MAX NUMBER OF BENDS = 2
5. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.



8		
7		
6		
5		
4	22/06/20	Revised Note 5
3	10/03/20	Changed Dwg, Added Note
2	01/03/18	Added Drawing Text
1	4/14/16	Revised Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: N/A

**RESIDENTIAL RISER TYPE  
SANITARY SERVICE  
CONNECTION**

Date: Feb. 22, 2011

Drawing #: 7-201

Scale: N.T.S.




**NOTES:**

1. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.
2. SEWER SERVICE MUST BE PROPERLY CAPPED.
3. INSTALL SERVICE PIPE FROM PLUG TO THE BUILDING CONNECTION  
MIN SLOPE = 1.0%

8			<b>The City of Lloydminster</b>			
7	22/06/20	Revised Note 1				
6	05/05/20	Added Text		Checked by:	Approved by:	Drawn by:
5	11/03/20	Added Text, Rev. Notes				N / A
4	3/22/18	Revised Notes		<b>MULTI-FAMILY SANITARY SERVICE INSPECTION CHAMBER</b>		
3	22/11/16	Revised Notes				
2	14/04/16	Revised Notes				
1	24/02/15	Min slope, dwg title				
NO.	DATE	REVISION				
				Scale:		
			N.T.S.	Date:	Feb. 22, 2011	
				Drawing #:	7-202	







**NOTES:**

1. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.
2. INSTALL SERVICE PIPE FROM PLUG TO THE BUILDING CONNECTION.  
MIN SLOPE = 1.0%

8			<b>The City of Lloydminster</b>						
7									
6	22/06/20	Revised Note 1		Checked by:	Approved by:	Drawn by:			
5	11/03/20	Revised Notes & Dwg.				N / A			
4	28/11/18	Revised Notes & Painted Plug		<b>COMMERCIAL / INDUSTRIAL SANITARY SERVICE INSPECTION MANHOLE</b>					
3	28/06/16	Revised Notes					Date:	Feb. 22, 2011	
2	14/04/16	Revised Notes					Drawing #:	7-203	
1	24/02/15	Min slope, dwg no.							
NO.	DATE	REVISION							
				Scale:	N.T.S.				



SECTION B-B

NOTES:

1. TO BE UTILIZED FOR INSPECTION CHAMBERS PLACED IN A HARD SURFACE.
2. USE ROYAL PIPE SYSTEMS 71A08 OR APPROVED EQUIVALENT.

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: **A. EDWARDS**

**METAL DRIVEWAY  
BOX**

Date: **Nov 22, 2016**  
Drawing #: **7-204**


8		
7		
6		
5		
4		
3		
2	05/05/20	Rev. Text Size & Style
1	11/03/20	REV. TEXT SIZE & STYLE
NO.	DATE	REVISION

Scale: **N.T.S.**



**NOTES:**

1. ALL TRENCH WALLS SHALL BE SLOPED OR SHORED IN CONFORMANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY REGULATIONS CURRENTLY IN EFFECT
2. OD = OUTSIDE DIAMETER
3. SERVICE CONNECTIONS TO BE MADE BETWEEN THE 10:00 AND 2:00 POSITION.
4. INSTALL 100mm SERVICE PIPE FROM PLUG TO THE HOUSE CONNECTION.  
 MIN SLOPE = 2.0%  
 MAX BEND = 45° TOTAL  
 MAX NUMBER OF BENDS = 2
5. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.



**SECTION A-A**

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: N / A


**RESIDENTIAL NON - RISER TYPE STORM SERVICE CONNECTION**

Date: Feb. 22, 2011

Drawing #: 7-300


Scale: N.T.S.

8		
7		
6		
5	22/06/20	Revised Note 5
4	11/03/20	Added Note 5
3	11/28/18	Added Property Line
2	4/14/16	Revised Notes
1	08/04/14	Reduced min cover @ P/L
NO.	DATE	REVISION



**NOTES:**

1. ALL TRENCH WALLS SHALL BE SLOPED OR SHORED IN CONFORMANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY REGULATIONS CURRENTLY IN EFFECT
2. OD = OUTSIDE DIAMETER
3. SERVICE CONNECTIONS TO BE MADE BETWEEN THE 10:00 AND 2:00 POSITION.
4. INSTALL 100mm SERVICE PIPE FROM PLUG TO THE HOUSE CONNECTION.  
 MIN SLOPE = 2.0%  
 MAX BEND = 45° TOTAL  
 MAX NUMBER OF BENDS = 2
5. THE CITY OF LLOYDMINSTER ACCEPTS NO RESPONSIBILITY FOR THE CONSTRUCTION OR MAINTENANCE OF THE SERVICES BEYOND THE PROPERTY LINE.



**SECTION A-A**

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: N / A

**RESIDENTIAL RISER TYPE  
STORM SERVICE CONNECTION**

Date: Feb. 22, 2011


Drawing #: 7-301

Scale: N.T.S.


8		
7		
6		
5		
4	22/06/20	Revised Note 5
3	11/03/20	Revised Drawing & Notes
2	11/28/18	Revised Drawings & Title
1	4/14/16	Revised Notes
NO.	DATE	REVISION

**NOTES:**

1. ROOF LEADERS (DOWNSPOUTS) OR ANY OTHER STORM WATER SOURCE MUST NOT BE CONNECTED TO THE FOUNDATION DRAIN DISCHARGE COLLECTION SYSTEM.
2. THE AUXILIARY SURFACE DISCHARGE MUST BE INSTALLED TO PROVIDE AN OVERFLOW IN THE EVENT THAT THE STORM DRAINAGE SYSTEM CANNOT ACCOMMODATE FLOWS DUE TO BLOCKAGE OR OTHER PROBLEMS.
3. EVERY PART OF THE PLUMBING SYSTEM SHALL BE PROTECTED FROM FREEZING THROUGH THE USE OF AN APPROVED METHOD.
4. WEEPING TILES SHALL NOT BE CONNECTED TO THE SANITARY SYSTEM.
5. THE LOCATION OF THE POINT OF DISCHARGE SHALL BE DIRECTED AWAY FROM ADJACENT PROPERTIES.
6. THE DISCHARGE MAY NOT BE DIRECTED INTO THE SIDE YARD UNLESS THE SIDE YARD IS ADJACENT TO A STREET.
7. DISCHARGE MAY NOT BE DIRECTED ONTO A PERVIOUS GROUND SURFACE WITHIN ONE METRE (1m) OF ANY BUILDING.



**DETAIL A**



**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: N/A

**WEEPING TILE DISCHARGE TO STORM SERVICE**

Date: Feb. 22, 2011


Drawing #: 7-302

Scale: N.T.S.


8		
7		
6		
5		
4	05/05/20	Revised Text Height
3	11/03/20	Revised Text Height
2	21/10/16	Revised Notes
1	08/04/14	Removed San. service
NO.	DATE	REVISION

**NOTES:**

1. ROOF LEADERS (DOWNSPOUTS) OR ANY OTHER STORM WATER SOURCE MUST NOT BE CONNECTED TO THE FOUNDATION DRAIN DISCHARGE COLLECTION SYSTEM.
2. THE AUXILIARY SURFACE DISCHARGE MUST BE INSTALLED TO PROVIDE AN OVERFLOW IN THE EVENT THAT THE STORM DRAINAGE SYSTEM CANNOT ACCOMMODATE FLOWS DUE TO BLOCKAGE OR OTHER PROBLEMS.
3. EVERY PART OF THE PLUMBING SYSTEM SHALL BE PROTECTED FROM FREEZING THROUGH THE USE OF AN APPROVED METHOD.
4. WEEPING TILES SHALL NOT BE CONNECTED TO THE SANITARY SYSTEM.
5. THE LOCATION OF THE POINT OF DISCHARGE SHALL BE DIRECTED AWAY FROM ADJACENT PROPERTIES.
6. THE DISCHARGE MAY NOT BE DIRECTED INTO THE SIDE YARD UNLESS THE SIDE YARD IS ADJACENT TO A STREET.
7. DISCHARGE MAY NOT BE DIRECTED ONTO A PERVIOUS GROUND SURFACE WITHIN ONE METRE (1m) OF ANY BUILDING.




**DETAIL A**



8		
7		
6		
5		
4	05/05/20	Revised Text Height
3	11/03/20	Revised Text Height
2	21/10/16	Revised Notes
1	08/04/14	Removed San. service
NO.	DATE	REVISION

**The City of Lloydminster**





Checked by: *[Signature]* Approved by: *[Signature]* Drawn by: N/A

**GRANULAR DRAINAGE DISCHARGE TO STORM SERVICE**

Date: Feb. 22, 2011  
Drawing #: 7-303

**NOTES:**

1. ROOF LEADERS (DOWNSPOUTS) OR ANY OTHER STORM WATER SOURCE MUST NOT BE CONNECTED TO THE FOUNDATION DRAIN DISCHARGE COLLECTION SYSTEM.
2. THE AUXILIARY SURFACE DISCHARGE MUST BE INSTALLED TO PROVIDE AN OVERFLOW IN THE EVENT THAT THE STORM DRAINAGE SYSTEM CANNOT ACCOMMODATE FLOWS DUE TO BLOCKAGE OR OTHER PROBLEMS.
3. EVERY PART OF THE PLUMBING SYSTEM SHALL BE PROTECTED FROM FREEZING THROUGH THE USE OF AN APPROVED METHOD.
4. WEEPING TILES SHALL NOT BE CONNECTED TO THE SANITARY SYSTEM.
5. THE LOCATION OF THE POINT OF DISCHARGE SHALL BE DIRECTED AWAY FROM ADJACENT PROPERTIES.
6. THE DISCHARGE MAY NOT BE DIRECTED INTO THE SIDE YARD UNLESS THE SIDE YARD IS ADJACENT TO A STREET.
7. DISCHARGE MAY NOT BE DIRECTED ONTO A PERVIOUS GROUND SURFACE WITHIN ONE METRE (1m) OF ANY BUILDING, DIRECTLY TO PROPERTY LINE, OR OUTSIDE THE PROPERTY.



8		
7		
6		
5		
4	05/05/20	Revised Text Height
3	11/03/20	Revised Text Height
2	21/10/16	Revised Notes
1	16/11/15	Changed note number
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: N/A


**GRANULAR DRAINAGE OVERLAND DISCHARGE**  
**IF STORM SERVICE IS NOT AVAILABLE**

Date: Feb. 22, 2011  
 Drawing #: 7-304


Scale: N.T.S.

**NOTES:**

1. ROOF LEADERS (DOWNSPOUTS) OR ANY OTHER STORM WATER SOURCE MUST NOT BE CONNECTED TO THE FOUNDATION DRAIN DISCHARGE COLLECTION SYSTEM.
2. THE AUXILIARY SURFACE DISCHARGE MUST BE INSTALLED TO PROVIDE AN OVERFLOW IN THE EVENT THAT THE STORM DRAINAGE SYSTEM CANNOT ACCOMMODATE FLOWS DUE TO BLOCKAGE OR OTHER PROBLEMS.
3. EVERY PART OF THE PLUMBING SYSTEM SHALL BE PROTECTED FROM FREEZING THROUGH THE USE OF AN APPROVED METHOD.
4. WEEPING TILES SHALL NOT BE CONNECTED TO THE SANITARY SYSTEM.
5. THE LOCATION OF THE POINT OF DISCHARGE SHALL BE DIRECTED AWAY FROM ADJACENT PROPERTIES.
6. THE DISCHARGE MAY NOT BE DIRECTED INTO THE SIDE YARD UNLESS THE SIDE YARD IS ADJACENT TO A STREET.
7. DISCHARGE MAY NOT BE DIRECTED ONTO A PERVIOUS GROUND SURFACE WITHIN ONE METRE (1m) OF ANY BUILDING, DIRECTLY TO PROPERTY LINE, OR OUTSIDE THE PROPERTY.



**DETAIL A**



8		
7		
6		
5		
4	05/05/20	Revised Text Height
3	11/03/20	Revised Text Height
2	21/10/16	Revised Notes
1	16/11/15	Changed Note Number
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: N / A

**WEEPING TILE  
OVERLAND DISCHARGE**

**IF STORM SERVICE IS NOT AVAILABLE**

Date: Feb. 22, 2011  
Drawing #: 7-305





**NOTES:**

1. SERVICES TO BE INSTALLED AT RIGHT ANGLES TO WATERMANS WHERE POSSIBLE.
2. SERVICE BOXES TO BE INSTALLED PLUMB. 150mm ABOVE THE SIDEWALK/CURB WHEN THE SERVICE BOX IS IN THE EXTENDED POSITION.
3. SERVICE PIPE TO BE UNIFORM DIAMETER AND CONTINUOUS FROM UNION AT CC STOP TO WATER METER.
4. MINIMUM COVER OVER SERVICE PIPES TO BE 2.85m AT THE PROPERTY LINE.
5. THE END OF THE WATER SERVICE SHALL NOT BE CRIMPED CLOSED. PERMEABLE FILTER CLOTH WILL BE USED TO PREVENT INTRUSION OF DEBRIS AND TO ALLOW TESTING FLOW OF CURBSTOP.
6. INSTALL UNION 4.0m FROM CC.
7. SERVICE BOX TO BE ADJUSTED TO BE SET FLUSH WITH FINISHED SURFACE IN BOULEVARDS. IN CONCRETE DRIVE WAYS, SERVICE BOX IS TO EITHER BE SET FLUSH WITH FINISHED SURFACE OR RECESSED BENEATH A REMOVABLE CAP.
8. SEE DWG. 7-402 FOR SERVICE BOX DETAILS.

8			<b>The City of Lloydminster</b>		
7			Checked by:	Approved by:	Drawn by: <b>L. LEEPER</b>
6			<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;"> <h2 style="margin: 0;">RESIDENTIAL WATER SERVICE CONNECTION</h2> <p style="margin: 0;">Scale: N.T.S.</p> </div> <div style="text-align: right;"> <p style="margin: 0;">Date: <b>Feb. 22, 2011</b></p> <p style="margin: 0;">Drawing #: <b>7-400</b></p> </div> </div>		
5					
4	11/03/20	Revised Notes & Detail			
3	23/03/18	Revised Notes & Detail			
2	22/11/16	Revised Notes			
1	4/14/16	Revised Notes			
NO.	DATE	REVISION			




TABLE A

DEPTH OF COVER	ROD LENGTH	CASING LENGTH
2.4m	2.15m	1.97m
2.85m	2.60m	2.42m
3.0m	2.75m	2.57m
3.3m	3.05m	2.87m

8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: **L. LEEPER**




**SERVICE VALVE ROD FOR  
20mm, 25mm, 38mm, 50mm  
CURB STOPS**

Date: Feb. 22, 2011

Drawing #: **7-401**

FOR 20mm & 25mm VALVES

FOR 40mm & 50mm VALVES



**SMALL BOOT FOR 20mm & 25mm SERVICE**

**LARGE BOOT FOR 40mm & 50mm SERVICE**

**NOTES:**

1. THE EXTERIOR & INTERIOR OF THE BOTTOM BOX SHALL BE FACTORY COATED.
2. GREY CAST IRON SHALL CONFORM TO ASTM A-48 CLASS 25 (LATEST EDITION).
3. OPERATING RODS TO BE AS PER DWG 7-401.

8		
7		
6		
5	22/06/20	Underlined Detail Names
4	05/05/20	Changed Text Ht, Rem. "mm"
3	11/03/20	Changed Text Ht, Added Note 3
2	3/22/18	Revised Notes
1	2/3/17	Revised Lineweight
NO.	DATE	REVISION


**The City of Lloydminster**




Checked by:	Approved by:	Drawn by: A. Edwards
-------------	--------------	----------------------

<b>SERVICE BOX</b>	Date: Nov 23, 2016
	Drawing #: 7-402

Scale: N.T.S.




**TYPE A**  
2-3% OVERALL LOT SLOPE  
REAR TO FRONT DRAINAGE



**TYPE B**  
3-6% OVERALL LOT SLOPE  
REAR TO FRONT DRAINAGE


**NOTES:**

1. FRONT PROPERTY LINE.
2. REAR PROPERTY LINE.
3. TYPICAL RELATIVE HIGH POINT ACROSS YARD DRAINAGE MAY BE SPLIT FROM CENTER OR ALL SLOPED TO LOW SIDE. TYPICAL 2.0% MIN. CROSS YARD SLOPES.
4. 2% MIN. SLOPE AWAY FROM BLDG.
5. 3.0m @ 5% MIN. SLOPE FROM WALL TO PROPERTY LINE.
6. MINIMUM GARAGE SLAB ELEVATION TO BE SET 0.36m ABOVE HIGHEST FRONT CORNER LOT ELEVATION.
7. ALL INTERIOR SLOPES, INCLUDING CONCRETE DRIVEWAYS, SIDEWALKS AND PATIOS TO BE A MINIMUM OF 2%.
8. DRIVEWAY SLOPE SHOULD BE LESS THAN 8.3%. SLOPES GREATER THAN 10.0% REQUIRE APPROVAL FROM THE CITY.
9. WHERE DESIGN BACK OF LOT ELEVATIONS ARE MUCH MORE THAN 2% ABOVE FRONT, A 10m SECTION OF LOT CAN BE SLOPED AT 3% MIN.
10. WHERE LOT BEHIND HAS SPLIT DRAINAGE, THIS LOT MUST ACCOMMODATE THE DRAINAGE FROM THE REAR OF THE LOT BEHIND IT.
11. ESTABLISHING AND MAINTAINING LOT GRADING AND DRAINAGE IS THE RESPONSIBILITY OF THE PROPERTY OWNER.




8		
7		
6	05/05/20	Rev. Text Height
5	11/03/20	Revised Notes & Drawing
4	11/28/18	Revised Notes
3	1/27/17	Revised Notes
2	4/14/16	Revised Notes
1	08/06/15	Added min. drop to Note 5
NO.	DATE	REVISION


**The City of Lloydminster**



Checked by:	Approved by:	Drawn by: N/A
<b>LOT GRADING BACK TO FRONT DRAINAGE</b>		Date: Feb. 22, 2011
		Drawing #: 8-100




**TYPE W**  
**WALKOUT BASEMENT**  
**SPLIT DRAINAGE**



**TYPE D**  
**STANDARD SPLIT DRAINAGE**

**NOTES:**

1. FRONT PROPERTY LINE.
2. REAR PROPERTY LINE.
3. TYPICAL RELATIVE HIGH POINT ACROSS YARD DRAINAGE MAY BE SPLIT FROM CENTRE OR ALL SLOPED TO LOW SIDE. TYPICAL 1.5% MIN. CROSS YARD SLOPES.
4. 2% MIN. SLOPE AWAY FROM BLDG.
5. 3.0m @ 5% MIN. SLOPE FROM WALL TO PROPERTY LINE.
6. HIGH POINT - VARIES.
7. MINIMUM GARAGE SLAB ELEVATION TO BE SET 0.36m ABOVE HIGHEST FRONT CORNER LOT ELEVATION.
8. ALL INTERIOR SLOPES, INCLUDING CONCRETE DRIVEWAYS, SIDEWALKS AND PATIOS TO BE A MINIMUM OF 2%.
9. DRIVEWAY SLOPE SHOULD BE LESS THAN 8.3%. SLOPES GREATER THAN 10.0% REQUIRE APPROVAL FROM THE CITY.
10. HIGH POINT MAY BE AT FRONT, REAR, OR MID-POINT, DEPENDANT ON HOUSE DESIGN AND RELATIVE ELEVATIONS OF LOT CORNERS.
11. ESTABLISHING AND MAINTAINING LOT GRADING AND DRAINAGE IS THE RESPONSIBILITY OF THE PROPERTY OWNER.



8		
7		
6	05/05/20	Revised Text Height
5	11/03/20	Revised Notes and Drawing
4	11/29/18	Revised Notes
3	1/27/17	Revised Notes
2	4/14/16	Revised Notes
1	08/06/15	Added Min. drop to Note 5
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: N/A

**LOT GRADING**  
**SPLIT DRAINAGE**

Date:  
Feb. 22, 2011

Drawing #:  
8-101



**NOTES:**

1. SLOPE OF SHARED SWALE MUST BE CONSISTENT WITH THE DESIGN SIDE LOT SLOPE.
2. ROOF LEADERS MUST BE ANGLED IN THE DIRECTION OF FLOW.
3. ESTABLISHING AND MAINTAINING LOT GRADING AND DRAINAGE IS THE RESPONSIBILITY OF THE PROPERTY OWNER.

8		
7		
6		
5		
4		
3	22/06/20	Revised Notes Height
2	11/29/18	Revised Notes
1	02/03/16	Revised height req'd
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: **L. LEEPER**

Scale: **N.T.S.**

**SHARED DRAINAGE  
BETWEEN LOTS**

Date: **June 8, 2015**

Drawing #: **8-102**



**NOTES:**

1. SLOPE OF CONCRETE AT FINISHED DRIVEWAY TO MATCH DESIGN SLOPE OF FINISHED GRADE.

8		
7		
6		
5		
4		
3	05/05/20	Revised Hatch Style
2	11/03/20	Revised Drawing
1	11/29/18	Revised Drawing
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: **A. EDWARDS**

**CONCRETE BETWEEN DRIVEWAYS**

Date: **Jan 26 2017**




Drawing #: **8-103**

Scale: **N.T.S.**




**NOTES:**


1. CONCRETE TO BE TYPE HS, 32 MPa COMPRESSIVE STRENGTH AT 28 DAYS WITH 5% TO 8% AIR ENTRAINMENT.
2. COMPACT BACKFILL TO 95% FOR 500mm FROM BACK OF SWALE AND PROVIDE POSITIVE DRAINAGE OVER THE TOP OF SWALE.
3. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.
4. EXPANSION JOINTS TO BE CONSTRUCTED AT ENDS OF SWALE WHERE SWALE ABUTS GUTTERS.

8			<b>The City of Lloydminster</b>			
7			 Scale: <b>N.T.S.</b>	Checked by: 	Approved by: 	Drawn by: <b>L. LEEPER</b>
6	11/03/20	Revised Slope Text & Hatch		<b>CONCRETE DRAINAGE SWALE (LANDSCAPING)</b>		
5	01/04/19	Revised Drawings				
4	11/29/18	Revised Notes & Drawings				
3	4/14/16	Revised Notes				
2	10/12/13	Updated concrete notes				
1	21/03/13	Updated concrete type				
NO.	DATE	REVISION	Date: <b>Feb. 22, 2011</b> Drawing #: <b>8-200</b>			








### ASPHALT CROSS SECTION




### CONCRETE CROSS SECTION


**NOTES:**

1. WIDTH MAY VARY WITH LOCATION.
2. HORIZONTAL CLEARANCE MIN WIDTH OF 1000mm FROM EDGE OF TRAIL.
3. CONTRACTION JOINTS 50mm DEEP AND 5mm WIDE TO BE CONSTRUCTED AT 3.0m INTERVALS.
4. ADJACENT GRADES ARE TO SLOPE AWAY FROM THE TRAIL WHEREVER POSSIBLE
5. CROSS-SLOPE TO BE IN THE DIRECTION OF SURFACE DRAINAGE (MIN. 2.0%).

8			<b>The City of Lloydminster</b>		
7				Checked by: 	Approved by: 
6				Drawn by: <b>L. LEEPER</b>	
5				Date: <b>Feb. 22, 2011</b>	
4	22/06/20	Revised Note 3		<b>STANDARD TRAIL</b>	
3	3/22/18	Revised Notes		Drawing #: <b>9-100</b>	
2	4/14/16	Revised Compaction %	Scale: <b>N.T.S.</b>		
1	24/03/14	Changed concrete strength			
NO.	DATE	REVISION			



ASPHALT CROSS SECTION





ELEVATION

NOTES:

1. DEPTH OF ROOT BARRIER VARIES ACCORDING TO PLANT AND MANUFACTURER'S RECOMMENDATIONS.
2. A TRENCH SHOULD BE DUG FOR THE ROOT BARRIER PRIOR TO IT BEING INSTALLED IN THE GROUND.
3. ROOT BARRIER SHOULD BE BURIED FLUSH WITH ROUGH GRADE.
4. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED.
5. TRAIL STRUCTURE AS PER DWG 9-100.

8				<b>The City of Lloydminster</b>			
7				Checked by:	Approved by:	Drawn by: A. EDWARDS	
6				<b>ROOT BARRIER SECTION AND ELEVATION</b>			
5							Date: Jan 5, 2017
4							Drawing #: 9-101
3							
2							
1	11/29/18	Revised Notes		Scale: N.T.S.			
NO.	DATE	REVISION					



**NOTES:**

1. PLANTING BED EDGE WILL MAINTAIN A GRADUAL ARC TO ACCOMMODATE TRACTOR MOWER TURNING.
2. ALL ASPHALT EDGES ARE TO BE FINISHED, AND NODE FREE OF ANY SEAMS.
3. FINISHED TOPSOIL GRADE TO BE MAINTAINED TO A MAXIMUM OF 12mm BELOW TOP OF FINISHED LEVEL OF ASPHALT SURFACE
4. TYPICAL PLANTING: 2 TREES & 16 SHRUBS
5. DIMENSIONS ARE IN MILLIMETRES.
6. SEE STANDARD DRAWING 9-305 FOR PLANTING BED DETAILS.

8		
7		
6		
5		
4		
3		
2		
1	17/03/20	Revised from Dwg. 9-103
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: J.IDIOH

Scale: N.T.S.

**TRAIL SEATING NODE**

Date: Jan. 14, 2019

Drawing #: 9-102



**NOTES:**

1. PRUNE SHRUBS & REGULARLY MOW GRASS BACK (IF REQUIRED) FROM EDGE TO TRAIL TO 1000mm MINIMUM
2. PROVIDE A MINIMUM HEADROOM CLEARANCE OF 2500mm AT CENTRE LINE OF TRAIL
3. WOVEN GEOTEXTILE MAT WITH MINIMUM TENSILE STRENGTH OF 91 KILOGRAMS OR BETTER
4. MULCH MATERIAL MUST COMPLY WITH SECTION 8.1.2.1
5. DIMENSIONS ARE IN MILLIMETRES

8		
7		
6		
5		
4		
3		
2		
1	17/03/20	Changed from Dwg. 9-104
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: J.IDIOH

**NATURE TRAIL**

Date: Jan. 07, 2019




Drawing #: 9-103

Scale: N.T.S.

R: 42  
G: 169  
B: 224

R: 13  
G: 118  
B: 189



8			<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: L. LEEPER
6				<p align="center"><b>PLAY SAFE SIGN</b> <b>18 MONTHS TO 5 YEARS</b></p>		
5			Date: Mar. 17, 2020			
4			Scale: N.T.S.	Drawing #: 9-104		
3						
2	05/05/20	Changed Title				
1	17/03/20	New Drawing				
NO.	DATE	REVISION				

R: 42  
G: 169  
B: 224

R: 13  
G: 118  
B: 189



8		
7		
6		
5		
4		
3		
2		
1		
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: L. LEEPER

**PLAY SAFE SIGN  
5 YEARS TO 12 YEARS**

Date: Mar. 15, 2020

Drawing #: 9-105



**NOTES:**

1. FASTENERS - SCREWS
  - RAIL TO POST: 3 #8 - 75mm D.S.
  - 3 #8 - 75mm D.S. (TOE NAIL)
  - RAIL TO FENCE BOARD:
    - FASTEN ALL FENCE BOARDS TO MIDDLE RAIL WITH 2 #6 - 50mm GREEN DECK SCREWS.
    - FASTEN MIDDLE & END FENCE BOARD TO ALL RAILS WITH 2 #6 - 87.5mm DECK SCREWS.
    - REMAINDER OF FENCE BOARDS TO BE SANDWICHED BETWEEN TOP & BOTTOM RAIL. ADD SCREWS AS REQUIRED FOR ANY LOOSE BOARDS.
2. USE GALVANIZED NAILS ONLY WHERE REQUIRED FOR FURTHER REINFORCEMENT. GALVANIZED - CSA G164

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: L. LEEPER

**WOODEN FENCE**

Date: Feb. 22, 2011  
 Drawing #: 9-200

8		
7		
6		
5		
4		
3	04/12/18	Changed reference information
2	08/04/14	Changed dimensions to metric
1	25/03/14	Moved fence 0.3m into city prop.
NO.	DATE	REVISION


Scale: N.T.S.






**NOTES:**

1. BOLLARD SPACING IS 1.2m O.C



TOP



ELEVATION

**The City of Lloydminster**

8		
7		
6		
5		
4	12/03/20	Specified Concrete Type
3	04/12/18	Revised Notes & Drawing Ref.
2	23/11/16	Revised Notes
1	08/04/14	Changed dimensions to metric
NO.	DATE	REVISION



Scale:  
N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: L. LEEPER

**6" X 6" WOOD BOLLARD**




Date:  
Feb. 22, 2011


Drawing #:  
**9-202**



**NOTES:**

1. BOLLARDS TO BE INSTALLED WITH 1.2m SPACING O.C

8			<b>The City of Lloydminster</b>						
7				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>			
6				<b>150mm STEEL LANDSCAPING BOLLARD</b>					
5	05/05/20	Removed "mm" Text					Date: <b>Nov 23, 2016</b> Drawing #: <b>9-203</b>		
4	12/03/20	Revised Drawing							
3	04/12/18	Revised Drawing and its ref.							
2	2/3/17	Revised Lineweight							
1	25/11/16	Changed bollard design	Scale: <b>N.T.S.</b>						
NO.	DATE	REVISION							



**NOTES:**

1. PLACE THE WASHER OVER THE PIPE OF THE TOP BAR AND INSERT INTO THE POST
2. INSERT THE PIN INTO THE FLANGES AND LOCK AT THE BOTTOM WITH KEY OR COMBINATION LOCK.
3. TOP BAR TO FEATURE 50mm REFLECTIVE TAPE ON BOTH SIDES.
4. ALL CUT EDGES TO BE GROUND TO A SMOOTH EDGE WITH NO SHARP ANGLES OR BURS.

8		
7		
6		
5		
4	12/03/20	Added Conc. Type & Clay Fill
3	26/06/19	Revised Notes
2	04/12/18	Revised Notes & Drawing Ref.
1	23/11/16	Revised Drawing Name
NO.	DATE	REVISION

**The City of Lloydminster**



Scale:  
N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: L. LEEPER

**SINGLE TRAFFIC  
CONTROL GATE**




Date:  
June 8, 2015




Drawing #:  
9-204



**NOTES:**




1. INSTALL THE GATES ACCORDING TO DRAWING 9-204.
2. GATES TO BE INSTALLED WITH A 1.2m OPENING BETWEEN BARS PRIOR TO INSTALLATION. CITY STAFF TO CONFIRM GATE OPENING DIMENSIONS.
3. TOP BAR TO FEATURE 50mm REFLECTIVE TAPE ON BOTH SIDES.
4. ALL CUT EDGES TO BE GROUND TO A SMOOTH EDGE WITH NO SHARP ANGLES OR BURS.


8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: A. EDWARDS
5				<b>PAIRED TRAFFIC CONTROL GATES</b>	Date: Nov 23, 2016	
4			Drawing #: 9-205			
3			Scale: N.T.S.			
2	26/06/19	Revised Notes				
1	12/04/18	Revised Notes & Drawing Ref.				
NO.	DATE	REVISION				



**NOTES:**




1. GATE FINISH TO BE BROWN ALKYD SEMI-GLOSS PAINT.
2. ALL WELDS TO BE GROUND SMOOTH.
3. PAINTING SHALL BE IN ACCORDANCE WITH C.P.C.A. (CANADIAN PAINTING CONTRACTORS ASSOCIATION)
4. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED.
5. TOP BAR TO FEATURE 50mm REFLECTIVE TAPE ON BOTH SIDES.


8				<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>	
6				<b>STEEL PIPE GATE</b>			
5							Date: <b>Jan 3, 2017</b>
4							Drawing #: <b>9-206</b>
3							
2	12/03/20	Specified Conc. Type					
1	12/04/18	Revised Drawing Reference		Scale: <b>N.T.S.</b>			
NO.	DATE	REVISION					



**NOTES:**

1. ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.






8				<b>The City of Lloydminster</b>		
7				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>
6				<b>CHAIN LINK MAINTENANCE GATE</b>		
5						
4						
3						
2	12/03/20	Specified Conc. Type				
1	12/04/18	Revised Drawing Reference		Scale: <b>N.T.S.</b>	Date: <b>Jan 3, 2017</b>	Drawing #: <b>9-207</b>
NO.	DATE	REVISION				



**NOTES:**

1. HEIGHT OF FENCE ABOVE GROUND IS NOMINAL AND SHALL BE VARIED TO ACHIEVE A SATISFACTORY VERTICAL ALIGNMENT.
2. POSTS AND RAILS TO BE CHAMFERED AS NECESSARY AT CHANGES OF DIRECTION.
3. POSTS TO BE LOCATED INSIDE CITY PROPERTY BY 150mm.
4. TOPS OF POSTS TO BE CHAMFERED 25mm.
5. MAIN POSTS AND STIFFENING PANEL TO BE PROVIDED AT ENDS (ONE PANEL) AND AT ALL CHANGES OF DIRECTION EXCEEDING 380mm VERTICALLY AND/OR 760mm HORIZONTALLY (ONE PANEL AT EACH SIDE OF MAIN POSTS.)
6. DOUBLE POSTS TO BE PROVIDED AS REQUIRED TO FACILITATE FENCING AROUND RADII.
7. TYPE HS 20 MPa CONCRETE SHALL BE USED FOR ALL FOUNDATIONS.
8. THE GROUND SHALL BE TRIMMED WHERE NECESSARY FOR THE BOTTOM OF THE FENCE.
9. POST HOLES TO BE RAMMED/BACKFILLED WITH SELECTED EXCAVATED MATERIAL NO SOONER THAN 24 HOURS AFTER PLACING CONCRETE.
10. ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE STATED.

8				<b>The City of Lloydminster</b>			
7				Checked by:	Approved by:	Drawn by: <b>A. EDWARDS</b>	
6				<b>WOODEN POST AND 3 RAIL FENCE</b>			
5							Date: <b>Jan 4, 2017</b>
4							Drawing #: <b>9-208</b>
3							
2	12/03/20	Specified Conc. Type					
1	12/04/18	Revised Notes & Drawing Ref					
NO.	DATE	REVISION	Scale: <b>N.T.S.</b>				



**NOTES:**

1. ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.

8		
7		
6		
5		
4	05/05/20	Rem. Dim. & "mm" From Dims.
3	12/03/20	Specified Conc. Type
2	04/01/19	Revised Drawings
1	12/04/18	Revised Drawings and Notes
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: **A. EDWARDS**




**NOISE ATTENUATION FENCE**

Date: **Jan 12, 2017**

Drawing #: **9-209**

Scale: **N.T.S.**





**The City of Lloydminster**

*Planning & Engineering*



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: L. LEEPER




**TREE GRATE 1500mm**

Date: Feb. 22, 2011

Drawing #: 9-300




Scale: N.T.S.



8		
7		
6		
5		
4		
3		
2		
1	05/05/20	Rem Dwg Path & "mm" from Dim
NO.	DATE	REVISION



**NOTES:**

1. PROVIDE A TAPER TO THE BERM ADJACENT TO THE BOULEVARD & PUBLIC UTILITY LOT/M.R. FOR MOWER TRANSITION.
2. A TRANSITION IS NOT REQUIRED IF A LANE IS CONSTRUCTED ADJACENT TO THE BERM.
3. ALL DIMENSIONS IN METRES


8			<b>The City of Lloydminster</b>			
7						
6				Checked by: 	Approved by: 	Drawn by: <b>A. EDWARDS</b>
5	05/05/20	Changed Plan View		<b>TYPICAL BERM</b>		
4	12/03/20	Removed Elev. View				
3	02/07/19	Revised Drawing				
2	04/01/19	Revised Drawing				
1	12/04/18	Revised Drawing & Removed Ref.				
NO.	DATE	REVISION	Scale: <b>N.T.S.</b>			Date: <b>Dec 29, 2016</b>
						Drawing #: <b>9-301</b>



**NOTES:**




1. SEE SECTION 8.1.2.1 FOR DETAILED PLANTING REQUIREMENTS
2. HOLE WIDTH EXCAVATION TO EQUAL 1.5 TIMES THE ROOT BALL DIAMETER.
3. FOR DECIDUOUS MATERIAL OVER 60mm, A MINIMUM CANOPY CLEARANCE OF 1.2m IS REQUIRED
4. THE ROOT FLARE OF NEWLY PLANTED TREES MUST BE VISIBLE AT TIME OF INSTALLATION


8			<b>The City of Lloydminster</b>	Checked by:		Approved by:		Drawn by:	J.IDIOH			
7					<b>WIRE BASKET TREE SPADE PLANTING TREE STAKING &amp; MULCHING</b>				Date:	Jan. 08, 2019		
6									Scale:	N.T.S.	Drawing #:	9-302
5												
4												
3												
2												
1	12/03/20	Added Hatching										
NO.	DATE	REVISION										



**NOTES:**

1. SEE SECTION 8.1.2.1 FOR DETAILED PLANTING REQUIREMENTS

8				<b>The City of Lloydminster</b>		
7				Checked by: 	Approved by: 	Drawn by: J.IDIOH
6				<b>TYPICAL CONTAINER PLANTING</b>		
5						
4						
3						
2						
1	12/03/20	Added Hatching		Scale: N.T.S.	Date: Jan. 08, 2019	Drawing #: 9-303
NO.	DATE	REVISION				



**NOTES:**

1. SEE SECTION 8.1.2.1 FOR DETAILED PLANTING REQUIREMENTS
2. DEPTH OF HOLE TO INCLUDE TOTAL DEPTH OF ROOT BALL & DEPTH OF MULCH.
3. PREPARE PLANTING SOIL AS SPECIFIED IN SECTION 8.1.2.1
4. FOR DECIDUOUS MATERIAL OVER 60mm, A MINIMUM CANOPY CLEARANCE OF 1.2m IS REQUIRED
5. THE ROOT FLARE OF NEWLY PLANTED TREES MUST BE VISIBLE AT TIME OF INSTALLATION

8		
7		
6		
5		
4		
3		
2		
1	12/03/20	Revised Fill Type
NO.	DATE	REVISION

**The City of Lloydminster**



Scale: N.T.S.

Checked by: *[Signature]*


Approved by: *[Signature]*

Drawn by: J.IDIOH

**TYPICAL VAULT PLANTING**




Date: Jan. 04, 2019


Drawing #: 9-304




**NOTES:**

1. SEE SECTION 8.1.2.1 FOR DETAILED PLANTING REQUIREMENTS
2. USE OF FILTER FABRIC AND EDGING WITHIN PLANTING BEDS IS NOT PERMITTED.
3. TOPSOIL MUST BE FREE OF STONES LARGER THAN 25mm IN DIAMETER, DEBRIS, QUACK GRASS, NOXIOUS WEEDS, OTHER PLANTS AND INORGANIC MATTER .
4. NO ANNUAL PLANTINGS ARE ALLOWED IN PLANTING BEDS, ONLY PERENNIALS AND BULBS
5. SHRUBS ARE TO BE PLANTED AT A RATE OF 5 PER SQUARE METRE
6. MULCH MAY BE: - BARK CHIPS FROM 25 TO 100mm IN DIAMETER  
 - WOOD CHIPS FROM 50 TO 100mm IN LENGTH AND 5 TO 20mm THICK  
 - SHREDDED WOOD FROM 25 TO 100mm IN LENGTH.
7. USE OF FILTER FABRIC AND EDGING WITHIN PLANTING BEDS IS NOT PERMITTED.


8			<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: J.IDIOH
6				<b>PLANTING BED CROSS-SECTION</b>		
5			Scale: N.T.S.	Date: Jan. 04, 2019		<b>9-305</b>
4				Drawing #:		
3	05/05/20	Added Note 7				
2	12/03/20	Added Hatching				
1						
NO.	DATE	REVISION				




TOP VIEW



SIDE ELEVATION



FRONT ELEVATION






ISOMETRIC VIEW


**NOTES:**

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. BENCH TO BE MOUNTED ON A CONCRETE PAD


**SPECIFICATIONS:**

- RECYCLED PLASTIC SLATS, OR APPROVED EQUIVALENT
- POWDER COATED ALUMINIUM FRAME, BLACK IN COLOUR
- STAINLESS STEEL HARDWARE


8			<b>The City of Lloydminster</b>			
7				Checked by: 	Approved by: 	Drawn by: A. EDWARDS
6				<b>TYPICAL PARK BENCH</b>		
5			Scale: N.T.S.			Date: Dec 5, 2016
4						Revision #: <b>9-400</b>
3						
2	12/04/18	Revised Drawing Title				
1	2/3/17	Revised Lineweight				
NO.	DATE	REVISION				




END VIEW



SIDE VIEW



PLAN VIEW



PLAN VIEW  
WHEELCHAIR ACCESSIBLE

**NOTES:**

1. FRAME TO BE MOUNTED TO A CONCRETE SLAB.

**SPECIFICATIONS:**

WOOD: 3 1/2" x 5 1/2" x 70" #1 GRADE SELECT CEDAR.

STEEL TYPE: 4" x 3" ANGLE IRON WOOD SUPPORTS.

2" x 2" SQUARE TUBE FRAME.

FASTENERS: 3/8" PLATED CARRIAGE BOLTS. COLOR MATCHED TO STEEL FRAME.

STEEL FINISH: POWDER COAT BLACK IN COLOR.

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: **A. EDWARDS**

**TYPICAL PICNIC TABLE**





Date: **Dec 5, 2016**  
Drawing #: **9-401**

8		
7		
6		
5		
4	23/06/20	Added Dimensions
3	05/05/20	Removed Dimensions
2	12/04/18	Revised Drawing Title
1	2/3/17	Revised Lineweight
NO.	DATE	REVISION

Scale: **N.T.S.**



FEATURE	DESCRIPTION	SPECIFICATION
Capacity	Tilt Out Bag Cage	9-1/2cu.ft. 70 Gallons (265L)
	Poly Bag	2.5mm 42"x50" (1070x1270)
Construction	Housing	12Ga. (2.6) Galvanneal Steel
	Lid	14Ga. (1.9) Galvanneal Steel
	User Door	14Ga. (1.9) Galvanneal Steel
	Side Hinged Unloading Door	14Ga. (1.9) Galvanneal Steel
	Hinges and Latches	Stainless Steel
	Paint	Powder Coat



8		
7		
6		
5		
4		
3		
2		
1	2/3/17	Revised Lineweight
NO.	DATE	REVISION

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*


Drawn by: **A. EDWARDS**

**GARBAGE RECEPTACLE**

Date: **Dec 21, 2016**

Drawing #: **9-402**

Scale: **N.T.S.**



**NOTES:**

1. PRATICA DISPENSER (201/203)
2. U-CHANNEL TO BE EMBEDDED WITHIN CONCRETE BASE, EXTENDING 200 mm ABOVE FINISHED GROUND
3. MOUNT DISPENSER ON U-CHANNEL POST. SECURE POST TO U-CHANNEL IN CONCRETE BASE

**The City of Lloydminster**



Checked by: *[Signature]*

Approved by: *[Signature]*

Drawn by: **A. EDWARDS**

**DOG WASTE BAG DISPENSER**

Date: **Dec 21, 2016**  
 Drawing #: **9-403**

8		
7		
6		
5		
4		
3	12/03/20	Rev. Note 2, Added Hatch
2	12/05/18	Revised Notes and Drawing Ref
1	2/3/17	Revised Lineweight
NO.	DATE	REVISION

Scale: **N.T.S.**